


Intended use

Mipa 2K Beschleuniger (2K-PU-Acellerator) used to speed up the drying process of Mipa 2K-paints. For example, Mipa OC, Mipa PUR HS and all Mipa 2K clearcoats.

Attention: Pot life is reduced.

Processing instructions



Mixing ratio

by weight (lacquer : acellerator)

by volume (lacquer : acellerator)

add at most 4% to the basic paint

--



Hardener

see tech sheet basic product



Pot life

see tech sheet basic product



Thinner

see tech sheet basic product

Storage: at least 2 years in unopened original container

VOC Regulation: less exempt solvents 857 g/l / 7.2 lb/gl
with exempt solvents 857 g/l / 7.2 lb/gl

Special notes: For professional use only. Not for sale to or use by the general public. Before opening the packages be sure you understand the warning Messages on the Labels and Safety Data Sheets of all components since the mixture will have the hazards of all of its parts. The manufacturer recommends the use of an air supplied Respirator when exposed to vapors or spray mist.

Medical Response:

Emergency Medical or Spill Control Information 011 49(0)700 24112112 (MIP)
US Emergency Phone Number (for transportation incidents only) 1-800-535-5053 (Infotrac)

Exclusive Importer: Fleetwood Products

3 American Way, Suite 15, Spotswood, NJ 08884 www.mipa-usa.com
fleetwood@mipa-usa.com 732-416-9590 Phone, 732-416-9592 Fax.