

Intended use





Mipa 2K-Löser is a special mixture of solvents (fade out thinner) to dissolve edges of spot repairs and fade-out areas for Mipa 2K topcoat systems. Mipa 2K-Löser can be added in combination with following products.

Mipa OC, Mipa PUR HS, Mipa PU 240, Mipa PU 257 and all Mipa 2K MS and HS clearcoats.

After having applied one of these products, spray immediately Mipa 2K-Löser over the border areas (overspray areas). We recommend to add Mipa 2K-Löser to a small rest of applied product.

Ratio: Rest of paint + appr. 200% Mipa 2K-Löser.

Processing instructions

	Mixing ratio	By volume (rest of used paint : 2K-Löser) 1 fl oz : 2 fl oz
	Hardener	--
	Pot life	--
	Thinner	--

Storage: at least 3 years in unopened original container

VOC Regulation: VOC as packaged:
less exempt solvents 934 g/l / 7.8 lb/gl
with exempt solvents 953 g/l / 8.0 lb/gl

Always check local VOC laws to ensure that the use of Mipa products is compliant in your area.

Special notes: It is not recommended to add Mipa 2K-Reaktivzusatz VR in matted 2K paints or clearcoats, because the reduced pot life may cause patches on the coating during drying.

For professional use only. Not for sale to or use by the general public.
Before opening the packages be sure you understand the warning Messages on the Labels and Safety Data Sheets of all components since the mixture will have the hazards of all of its parts. The manufacturer recommends the use of an air supplied Respirator when exposed to vapors or spray mist.

Medical Response:
Emergency Medical or Spill Control Information 011 49(0)700 24112112 (MIP)
US Emergency Phone Number (for transportation incidents only) 1-800-535-5053 (Infotrac)

Exclusive Importer: Fleetwood Products
3 American Way, Suite 15, Spotswood, NJ 08884 www.mipa-usa.com
fleetwood@mipa-usa.com. 732-416-9590 Phone, 732-416-9592 Fax.

Version: US 0418

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

MIPA SE · Am Oberen Moos 1 · D-84051 Essenbach · Tel.: +49(0)8703/922-0 · Fax: +49(0)8703/922-100 · mipa@mipa-paints.com · www.mipa-paints.com