

Intended use









Mipa 2K-Löser is a special mixture of solvents (fade-out thinner) to "melt" edges of spot repairs and fade-out areas. Mipa 2K-HS-Löser can also be used to dissolve an old paintworks (Attention: test suitability to avoid unwanted wrinkling/raising of old paintwork) in order to improve the adhesion of the subsequent coating. In this case, Mipa 2K-Löser must be applied uniformly on the old paintwork and recoated within a few minutes. Mipa 2K-Löser can be used as fade-out thinner in combination with following products:

Mipa AC, Mipa PUR-HS, Mipa OC, Mipa 2K-MS and HS Clearcoats

After having applied one of these products, spray immediately Mipa 2K-Löser over the border areas (overspray areas). Melt the overspray edges with a very uniform coat of Mipa 2K-Löser until the rough overspray become visibly smooth. Do not apply too much, otherwise irregular dissolving or runs are to be expected.

Spreading rate: --

General informations

	Colour colourless					
	Mixing ratio	Hardener		by weight (lacquer : hardener)	by volume (lacquer : hardener)	
	--	--	--	--	--	
	Hardener	for complete paintwork		for partial paintwork		
	--	--		--		
	Pot life --					
	Thinner ready for use					
	Spray viscosity	gravity spray gun		Airmix/Airless		
	--	--		--		
	Application mode	Application mode	Hardener	pressure (bar)	nozzle (mm)	spray passes
	--	--	--	--	--	--
	Flash-off time --					

Dry coat thickness						
--						



Drying time
 object
 temperature

--

dust dry

--

**set to
 touch**

--

**ready for
 assembly**

--

sandable

--

recoatable

--

Note

Storage: at least 4 years in unopened original containers

VOC Information: --

Processing conditions: In tightly closed original containers at least 4 years shelf life.
 Storage temperature range 50 - 86°F (10 - 30 °C)
 Protect package from direct sunlight and heat.

General informations: Do not apply on thermoplastic substrates.

Safety aspect:

For professional use only. Not for sale to or use by the general public. Before opening the packages be sure you understand the warning Messages on the Labels and Safety Data Sheets of all components since the mixture will have the hazards of all of its parts. The manufacturer recommends the use of an air supplied Respirator when exposed to vapors or spray mist.

Medical Response:

Emergency Medical or Spill Control Information 011 49(0)700 24112112 (MIP)
 US Emergency Phone Number (for transportation incidents only) 1-800-535-5053 (Infotrac)

Exclusive Importer: Mipa USA Inc

3 American Way, Suite 15, Spotswood, NJ 08884 www.mipa-usa.com
Info@mipa-usa.com. 732-416-9590 Phone, 732-416-9592