










Intended use

Mipa WBS Cleaner LV is a VOC compliant waterborn degreaser. Used for the cleaning of old paint and filler areas before top coat application. Mipa WBS Cleaner LV provides a residue free cleaning with different cleaning wipes.

Antistatic effect specially on plastic parts.

Spreading rate: --

General informations

	Colour	--				
	Mixing ratio	--				
	Hardener	by weight (lacquer : hardener)		by volume (lacquer : hardener)		
		--		--		
	Hardener	--				
	for complete paintwork	for partial paintwork				
		--				
	Pot life	--				
	Thinner	--				
	Spray viscosity	--				
	gravity spray gun	Airmix/Airless				
		--				
	Application mode	--				
	Application mode	Hardener	pressure (bar)	nozzle (mm)	spray passes	Thinner
		--	--	--	--	--
	Flash-off time	--				
		--				
	Dry coat thickness	--				
		--				
	Drying time	--				
	object temperature	dust dry	set to touch	ready for assembly	sandable	recoatable
		--	--	--	--	--

Note

- Storage:** In tightly closed original containers at least 3 years shelf life.
Storage temperature range 50 - 86°F (10 - 30 °C)
Protect package against frost.
- VOC Information:** VOC as packaged:
less exempt solvents 194 g/l / 1.6 lb/gl
with exempt solvents 446 g/l / 3.7 lb/gl
- Always check local VOC laws to ensure that the use of Mipa products is compliant in your area
- Processing conditions:** from 50 °F (10 °C) and up to 80 % relative air humidity.
Ensure an adequate supply and exhaust air ventilation.
- General informations:** Blow off all residual moisture from corners, edges and grooves with air pressure.
- We recommend application by MP Pump Sprayer.
- Safety aspect:
For professional use only. Not for sale to or use by the general public. Before opening the packages be sure you understand the warning Messages on the Labels and Safety Data Sheets of all components since the mixture will have the hazards of all of its parts. The manufacturer recommends the use of an air supplied Respirator when exposed to vapors or spray mist.
- Medical Response:
Emergency Medical or Spill Control Information 011 49(0)700 24112112 (MIP)
US Emergency Phone Number (for transportation incidents only) 1-800-535-5053 (Infotrac)
- Exclusive Importer: Fleetwood Products
3 American Way, Suite 15, Spotswood, NJ 08884 www.mipa-usa.com
fleetwood@mipa-usa.com. 732-416-9590 Phone, 732-416-9592 Fax.