Fleetwood Products Inc.

Tel.: +1 7324169590

13 American Way Suite 15 USA - NJ 08884 Spotswood

e.mail: fleet089@hotmail.com



# Safety Data Sheet

acc. to OSHA HCS

Reviewed on 11/06/2023 Printing date 11/06/2023

#### 1 Identification

- · Product identifier
- Trade name: Mipa 2K-Beschleuniger
- · Application of the substance / the mixture Accelerator
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49(0)8703-922-0

Fax.: +49(0)8703-922-100

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

Emergency telephone number:

International: 011 49(0)700 24112112 (MIP)

US: +1 872 5888271 (MIP)

US Emergency Telephone Number (for transportation incidents only): 1-800-535-5053 (Infotrac)

## 2 Hazard(s) identification

#### · Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS08 Health hazard

Germ Cell Mutagenicity 2 H341 Suspected of causing genetic defects. Toxic to Reproduction 1B H360 May damage fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure 1 H370 Causes damage to organs.

Specific Target Organ Toxicity - Repeated Exposure 1

H372 Causes damage to the immune system through prolonged or repeated exposure.



GHS07

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

(Contd. on page 2)



acc. to OSHA HCS

Printing date 11/06/2023 Reviewed on 11/06/2023

Trade name: Mipa 2K-Beschleuniger

(Contd. of page 1)

#### · Hazard-determining components of labeling:

n-Butyl acetate dibutyltin dilaurate

#### · Hazard statements

H226 Flammable liquid and vapor.

H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.

H360 May damage fertility or the unborn child.

H370 Causes damage to organs.

H336 May cause drowsiness or dizziness.

H372 Causes damage to the immune system through prolonged or repeated exposure.

#### · Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a poison center/doctor if you feel unwell.

#### · Classification system:

· NFPA ratings (scale 0 - 4)



Health = 0 Fire = 3 Reactivity = 0

#### · HMIS-ratings (scale 0 - 4)



Health = \*0 Fire = 3 Reactivity = 0

- · Other hazards
- Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
123-86-4	n-Butyl acetate	50-100%
77-58-7	dibutyltin dilaurate	2.5-<10%

#### 4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.

(Contd. on page 3)



acc. to OSHA HCS

Printing date 11/06/2023 Reviewed on 11/06/2023

Trade name: Mipa 2K-Beschleuniger

(Contd. of page 2)

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:		
123-86-4	n-Butyl acetate	5 ppm
77-58-7	dibutyltin dilaurate	1.1 mg/m³
PAC-2:		
123-86-4	n-Butyl acetate	200 ppm
77-58-7	dibutyltin dilaurate	8 mg/m³
· PAC-3:		
123-86-4	n-Butyl acetate	3000* ppm
77-58-7	dibutyltin dilaurate	48 mg/m³

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

(Contd. on page 4)



acc. to OSHA HCS

Printing date 11/06/2023 Reviewed on 11/06/2023

Trade name: Mipa 2K-Beschleuniger

(Contd. of page 3)

#### · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

#### · Components with limit values that require monitoring at the workplace:

#### 123-86-4 n-Butyl acetate

PEL Long-term value: 710 mg/m³, 150 ppm

REL Short-term value: 950 mg/m³, 200 ppm

Long-term value: 710 mg/m³, 150 ppm

TLV Short-term value: 150 ppm Long-term value: 50 ppm

#### 77-58-7 dibutyltin dilaurate

PEL Long-term value: 0.1 mg/m3

as Šn

REL Long-term value: 0.1 mg/m³

as Sn, Skin

TLV | Short-term value: 0.2 mg/m<sup>3</sup>

Long-term value: 0.1 mg/m<sup>3</sup>

as Sn; A4; Skin

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· Breathing equipment:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

#### Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 5)



acc. to OSHA HCS

Printing date 11/06/2023 Reviewed on 11/06/2023

Trade name: Mipa 2K-Beschleuniger

(Contd. of page 4)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



#### Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Eye protection:

· Vapor density · Evaporation rate



Tightly sealed goggles

## 9 Physical and chemical properties

· Information on basic physical and c · General Information	Information on basic physical and chemical properties General Information		
· Appearance:			
Form:	Fluid		
Color:	According to product specification		
· Odor:	Characteristic		
Odor threshold:	Not determined.		
· pH-value:	Not determined.		
· Change in condition			
Melting point/Melting range:	Undetermined.		
Boiling point/Boiling range:	124-128 °C (255.2-262.4 °F)		
· Flash point:	25 °C (77 °F) (DIN 53213)		
· Flammability (solid, gaseous):	Flammable.		
· Auto igniting:	370 °C (698 °F) (DIN 51794)		
Decomposition temperature:	Not determined.		
· Ignition temperature:	Product is not selfigniting.		
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.		
· Explosion limits:			
Lower:	1.2 Vol %		
Upper:	7.5 Vol %		
Vapor pressure at 20 °C (68 °F):	10.7 hPa /8 mm Ha)		
	10.7 hPa (8 mm Hg)		
· Vapor pressure at 50 °C (122 °F):	55 hPa (41.3 mm Hg)		
· Density at 20 °C (68 °F):	0.884 g/cm³ (7.377 lbs/gal) (DIN 53217)		
Relative density	Not determined.		
Managaratan atta	Aladada ka wasan a al		

Not determined.

Not determined.

(Contd. on page 6)



acc. to OSHA HCS

Printing date 11/06/2023 Reviewed on 11/06/2023

Trade name: Mipa 2K-Beschleuniger

		(Contd. of page 5
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wa	ater): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic at 20 °C (68 °F):	15 s (DIN 53211/4)	
· Solvent content:		
VOC content:	97.50 %	
	862 g/l / 7.2 lb/gal	
Solids content (weight-%):	2.5 %	
· Other information	No further relevant information available.	

# 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

#### 123-86-4 n-Butyl acetate

Oral LD50 13,100 mg/kg (rat)
Dermal LD50 >5,000 mg/kg (rabbit)

- Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 7)



acc. to OSHA HCS

Printing date 11/06/2023 Reviewed on 11/06/2023

Trade name: Mipa 2K-Beschleuniger

(Contd. of page 6)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

#### 14 Transport information

· UN-Number · DOT, ADR, IMDG, IATA	UN1263
· UN proper shipping name	
DOT	Paint related material
· ADR	UN1263 PAINT RELATED MATERIAL,
	ENVIRONMENTALLY HAZARDOUS
· IMDG	PAINT RELATED MATERIAL (dibutyltin dilaurate),
	MARINE POLLUTANT
· IATA	PAINT RELATED MATERIAL

· Transport hazard class(es)

· DOT



Class 3 Flammable liquids

(Contd. on page 8)



# Safety Data Sheet acc. to OSHA HCS

Reviewed on 11/06/2023 Printing date 11/06/2023

Trade name: Mipa 2K-Beschleuniger

	(Contd. of pag
Label	3
ADR	
Class Label	3 (F1) Flammable liquids 3
IMDG	
Class Label	3 Flammable liquids 3
IATA	
Class Label	3 Flammable liquids 3
Packing group DOT, ADR, IMDG, IATA	III
Environmental hazards:  Marine pollutant:	Product contains environmentally hazardo substances: dibutyltin dilaurate No Yes (DOT) Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	<i>Warning: Flammable liquids</i> 30 <i>F-E,<u>S-E</u> A</i>
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT Remarks:	Special marking with the symbol (fish and tree).
ADR Limited quantities (LQ)	5L
IMDG Limited quantities (LQ)	5L
UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, ENVIRONMENTALLY HAZARDOUS



acc. to OSHA HCS

Printing date 11/06/2023 Reviewed on 11/06/2023

Trade name: Mipa 2K-Beschleuniger

(Contd. of page 8)

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· Hazardous Air Pollutants

None of the ingredients is listed.

- Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Cancerogenity categories
- EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

77-58-7 dibutyltin dilaurate

A4 2.5-<10%

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

n-Butyl acetate

dibutyltin dilaurate

Hazard statements

H226 Flammable liquid and vapor.

H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.

H360 May damage fertility or the unborn child.

H370 Causes damage to organs.

H336 May cause drowsiness or dizziness.

H372 Causes damage to the immune system through prolonged or repeated exposure.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Contd. on page 10)



acc. to OSHA HCS

Printing date 11/06/2023 Reviewed on 11/06/2023

Trade name: Mipa 2K-Beschleuniger

(Contd. of page 9)

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a poison center/doctor if you feel unwell.

· National regulations:

· Additional classification according to Decree on Hazardous Materials:

Class	Share in %
NK	50-100

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Contact:
- · Date of preparation / last revision 11/06/2023
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit Flammable Liquids 3: Flammable liquids - Category 3

Sensitization - Skin 1: Skin sensitisation - Category 1

Germ Cell Mutagenicity 2: Germ cell mutagenicity - Category 2

Toxic to Reproduction 1B: Reproductive toxicity - Category 1B

Specific Target Organ Toxicity - Single Exposure 1: Specific target organ toxicity (single exposure) - Category 1 Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) - Category 1

\* Data compared to the previous version altered.