

## 1 Identification

· **Product identifier**

· **Trade name:** *Mipa 2K-HS-Grundfiller F 54*

· **Application of the substance / the mixture** *Filler*

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

MIPA SE

Am Oberen Moos 1

D-84051 Essenbach

Tel.: +49(0)8703-922-0

Fax.: +49(0)8703-922-100

e-mail: [sdb-registratur@mipa-paints.com](mailto:sdb-registratur@mipa-paints.com)

[www.mipa-paints.com](http://www.mipa-paints.com)

*Fleetwood Products Inc.*

*13 American Way Suite 15*

*USA - NJ 08884 Spotswood*

*Tel.: +1 7324169590*

*e.mail: [fleet089@hotmail.com](mailto:fleet089@hotmail.com)*

· **Emergency telephone number:**

*International: 011 49(0)700 24112112 (MIP)*

*US: +1 872 5888271 (MIP)*

*US Emergency Telephone Number (for transportation incidents only): 1-800-535-5053 (Infotrac)*

## 2 Hazard(s) identification

· **Classification of the substance or mixture**



GHS02 Flame

*Flammable Liquids 3*

*H226 Flammable liquid and vapor.*



GHS08 Health hazard

*Specific Target Organ Toxicity - Repeated Exposure 2*

*H373 May cause damage to the hearing organs through prolonged or repeated exposure.*



GHS07

*Skin Irritation 2*

*H315 Causes skin irritation.*

*Eye Irritation 2A*

*H319 Causes serious eye irritation.*

*Sensitization - Skin 1*

*H317 May cause an allergic skin reaction.*

· **Label elements**

· **GHS label elements**

*The product is classified and labeled according to the Globally Harmonized System (GHS).*

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** *Warning*

· **Hazard-determining components of labeling:**

*Xylene*

*Bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight 700-1100)*

*Ethylbenzene*

*Methyl methacrylate*

**Trade name: Mipa 2K-HS-Grundfiller F 54**

(Contd. of page 1)

**Hazard statements**

- H226 Flammable liquid and vapor.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H373 May cause damage to the hearing organs through prolonged or repeated exposure.

**Precautionary statements**

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P363 Wash contaminated clothing before reuse.

**Classification system:**

**NFPA ratings (scale 0 - 4)**



Health = 2  
Fire = 3  
Reactivity = 0

**HMIS-ratings (scale 0 - 4)**



Health = 2  
Fire = 3  
Reactivity = 0

**Other hazards**

**Results of PBT and vPvB assessment**

- PBT:** Not applicable.
- vPvB:** Not applicable.

**3 Composition/information on ingredients**

**Chemical characterization: Mixtures**

**Description:** Mixture of the substances listed below with nonhazardous additions.

**Dangerous components:**

123-86-4	n-Butyl acetate	≤20%
1330-20-7	Xylene	≥10-<15%
100-41-4	Ethylbenzene	2.5-<10%
25068-38-6	Bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight 700-1100)	≥1-<2.5%
80-62-6	Methyl methacrylate	≥0.1-<1%

**4 First-aid measures**

**Description of first aid measures**

**General information:** Immediately remove any clothing soiled by the product.

**After inhalation:**

Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:** Immediately rinse with water.

(Contd. on page 3)

Printing date 10/02/2024

Reviewed on 10/02/2024

**Trade name: Mipa 2K-HS-Grundfiller F 54**

(Contd. of page 2)

- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Alcohol resistant foam
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

### · PAC-1:

123-86-4	n-Butyl acetate	5 ppm
1330-20-7	Xylene	130 ppm
100-41-4	Ethylbenzene	33 ppm
25068-38-6	Bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight 700-1100)	90 mg/m <sup>3</sup>
80-62-6	Methyl methacrylate	17 ppm

### · PAC-2:

123-86-4	n-Butyl acetate	200 ppm
1330-20-7	Xylene	920* ppm
100-41-4	Ethylbenzene	1100* ppm
25068-38-6	Bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight 700-1100)	990 mg/m <sup>3</sup>
80-62-6	Methyl methacrylate	120 ppm

### · PAC-3:

123-86-4	n-Butyl acetate	3000* ppm
1330-20-7	Xylene	2500* ppm

(Contd. on page 4)

Printing date 10/02/2024

Reviewed on 10/02/2024

**Trade name: Mipa 2K-HS-Grundfiller F 54**

100-41-4	Ethylbenzene	(Contd. of page 3) 1800* ppm
25068-38-6	Bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight 700-1100)	5,900 mg/m <sup>3</sup>
80-62-6	Methyl methacrylate	570 ppm

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the remaining constituent has no known exposure limits.

### 123-86-4 n-Butyl acetate

PEL	Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
REL	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

### 1330-20-7 Xylene

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 20 ppm BEI, A4

### 100-41-4 Ethylbenzene

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 545 mg/m <sup>3</sup> , 125 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 20 ppm OTO, BEI, A3

(Contd. on page 5)

**Trade name: Mipa 2K-HS-Grundfiller F 54**

(Contd. of page 4)

**80-62-6 Methyl methacrylate**

PEL	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm
REL	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 100 ppm Long-term value: 50 ppm DSEN, A4

**Ingredients with biological limit values:**

**1330-20-7 Xylene**

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

**100-41-4 Ethylbenzene**

BEI	0.15 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)
-----	---

**Additional information:** The lists that were valid during the creation were used as basis.

**Exposure controls**

**Personal protective equipment:**

**General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the eyes.  
Avoid contact with the eyes and skin.

**Breathing equipment:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

**Protection of hands:**

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

**Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Breakthrough time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Printing date 10/02/2024

Reviewed on 10/02/2024

**Trade name: Mipa 2K-HS-Grundfiller F 54**

(Contd. of page 5)

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Fluid

Color:

According to product specification

· **Odor:**

Characteristic

· **Odor threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

124-128 °C (255.2-262.4 °F)

· **Flash point:**

24 °C (75.2 °F) (DIN EN ISO 1523:2002)

· **Flammability:**

Flammable.

· **Auto igniting:**

370 °C (698 °F) (DIN 51794)

· **Decomposition temperature:**

Not determined.

· **Ignition temperature:**

Product is not selfigniting.

· **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower:

1.1 Vol %

Upper:

7.5 Vol %

· **Vapor pressure at 20 °C (68 °F):**

10.7 hPa (8 mm Hg)

· **Vapor pressure at 50 °C (122 °F):**

55 hPa (41.3 mm Hg)

· **Density at 20 °C (68 °F):**

1.483 g/cm<sup>3</sup> (12.376 lbs/gal) (DIN EN ISO 2811-1)

· **Relative density**

Not determined.

· **Vapor density**

Not determined.

· **Evaporation rate**

Not determined.

· **Solubility in / Miscibility with**

Water:

Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic:

Not determined.

Kinematic at 20 °C (68 °F):

>60 s (ISO 6 mm)

· **Solvent content:**

VOC content:

32.40 %

481 g/l / 4.0 lb/gal

**Solids content (weight-%):**

67.6 %

(Contd. on page 7)



Printing date 10/02/2024

Reviewed on 10/02/2024

**Trade name: Mipa 2K-HS-Grundfiller F 54**

(Contd. of page 6)

· **Other information**

No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	Xylene	3
14807-96-6	Talc	3
13463-67-7	Titanium dioxide	2B
100-41-4	Ethylbenzene	2B
1333-86-4	Carbon black	2B
80-62-6	Methyl methacrylate	3

- **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO <sub>2</sub> )	K
14808-60-7	Quartz (SiO <sub>2</sub> )	K

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 8)

**Trade name: Mipa 2K-HS-Grundfiller F 54**




(Contd. of page 7)

- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1263
- **UN proper shipping name**
- **DOT** Paint
- **ADR** UN1263 PAINT
- **IMDG, IATA** PAINT
- **Transport hazard class(es)**
- **DOT**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **ADR**
- 
- **Class** 3 (F1) Flammable liquids
- **Label** 3
- **IMDG, IATA**
- 
- **Class** 3 Flammable liquids
- **Label** 3

(Contd. on page 9)



Printing date 10/02/2024

Reviewed on 10/02/2024

Trade name: Mipa 2K-HS-Grundfiller F 54

(Contd. of page 8)

· <b>Packing group</b>	
· <b>DOT, ADR, IMDG, IATA</b>	III
· <b>Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>Special precautions for user</b>	Warning: Flammable liquids
· <b>Hazard identification number (Kemler code):</b>	30
· <b>EMS Number:</b>	F-E, S-E
· <b>Stowage Category</b>	A
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Remarks:</b>	≤ 450 l: 2.2.3.1.5 ADR
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Remarks:</b>	≤ 450 l: 2.3.2.5 IMDG-Code
· <b>UN "Model Regulation":</b>	UN 1263 PAINT, 3, III

## 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

### · **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

### · **Section 313 (Specific toxic chemical listings):**

1330-20-7 Xylene

100-41-4 Ethylbenzene

80-62-6 Methyl methacrylate

### · **Hazardous Air Pollutants**

1330-20-7 Xylene

100-41-4 Ethylbenzene

80-62-6 Methyl methacrylate

### · **Proposition 65**

#### · **Chemicals known to cause cancer:**

100-41-4 Ethylbenzene

#### · **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

#### · **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

#### · **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

(Contd. on page 10)

**Trade name: Mipa 2K-HS-Grundfiller F 54**

(Contd. of page 9)

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	Xylene	I
100-41-4	Ethylbenzene	D
80-62-6	Methyl methacrylate	E, NL

· **TLV (Threshold Limit Value)**

1330-20-7	Xylene	A4	≥10-<15%
100-41-4	Ethylbenzene	A3	2.5-<10%
80-62-6	Methyl methacrylate	A4	≥0.1-<1%

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	Titanium dioxide
1333-86-4	Carbon black
14808-60-7	Quartz (SiO <sub>2</sub> )
14808-60-7	Quartz (SiO <sub>2</sub> )

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Warning

· **Hazard-determining components of labeling:**

Xylene  
Bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight 700-1100)  
Ethylbenzene  
Methyl methacrylate

· **Hazard statements**

H226 Flammable liquid and vapor.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H373 May cause damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P363 Wash contaminated clothing before reuse.

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials:**

Class	Share in %
NK	25-50

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

USA

(Contd. on page 11)

Printing date 10/02/2024

Reviewed on 10/02/2024

**Trade name: Mipa 2K-HS-Grundfiller F 54**

(Contd. of page 10)

## 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Contact:**

· **Date of preparation / last revision 10/02/2024 / 25**

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Skin 1: Skin sensitisation – Category 1

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2

· **\* Data compared to the previous version altered.**

USA