Fleetwood Products Inc.

Tel.: +1 7324169590

13 American Way Suite 15 USA - NJ 08884 Spotswood

e.mail: fleet089@hotmail.com



Safety Data Sheet

acc. to OSHA HCS

Reviewed on 06/09/2023 Printing date 06/09/2023

1 Identification

- · Product identifier
- · Trade name: Mipa 2K-HS-Härter HS 5
- · Application of the substance / the mixture Hardening agent/ Curing agent
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MIPA SE Am Oberen Moos 1 D-84051 Essenbach Tel.: +49(0)8703-922-0

Fax.: +49(0)8703-922-100 e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

Emergency telephone number:

International: 011 49(0)700 24112112 (MIP)

US: +1 872 5888271 (MIP)

US Emergency Telephone Number (for transportation incidents only): 1-800-535-5053 (Infotrac)

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

H334 May cause allergy or asthma Sensitization - Respiratory 1

symptoms or breathing difficulties if

inhaled.

Toxic to Reproduction 1B H360 May damage fertility or the unborn

child.



Acute Toxicity - Inhalation 4 Harmful if inhaled. H332

Eve Irritation 2A H319 Causes serious eye irritation.

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3 H335-H336 May cause respiratory irritation. May cause drowsiness or

dizziness.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07 GHS08



acc. to OSHA HCS

Printing date 06/09/2023 Reviewed on 06/09/2023

Trade name: Mipa 2K-HS-Härter HS 5

(Contd. of page 1)

· Signal word Danger

· Hazard-determining components of labeling:

Hexamethylene diisocyanate, oligomers

dibutyltin dilaurate

Ethyl acetate

n-Butyl acetate

Hazard statements

H225 Highly flammable liquid and vapor.

H332 Harmful if inhaled.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.
H360 May damage fertility or the unborn child.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

· Classification system:

NFPA ratings (scale 0 - 4)



Health = 2 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 3 Reactivity =

Y 0 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

	Dangerous components:		
28182-81-2 Hexamethylene diisocyanate, oligomers		50-100%	
	141-78-6	Ethyl acetate	25-50%
	123-86-4	n-Butyl acetate	5-<10%
	77-58-7	dibutyltin dilaurate	≥0.1-<1%
	4083-64-1	4-isocyanatosulphonyltoluene	≥0.1-<1%

- USA



acc. to OSHA HCS

Printing date 06/09/2023 Reviewed on 06/09/2023

Trade name: Mipa 2K-HS-Härter HS 5

(Contd. of page 2)

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:			
28182-81-2	Hexamethylene diisocyanate, oligomers	7.8 mg/m³	
141-78-6	Ethyl acetate	1,200 ppm	
123-86-4	n-Butyl acetate	5 ppm	
77-58-7	dibutyltin dilaurate	1.1 mg/m³	
822-06-0	hexamethylene-di-isocyanate	0.018 ppm	
		(Contd. on page	



acc. to OSHA HCS

Reviewed on 06/09/2023 Printing date 06/09/2023

Trade name: Mipa 2K-HS-Härter HS 5

		(Contd. of page 3
PAC-2:		
28182-81-2	Hexamethylene diisocyanate, oligomers	86 mg/m³
141-78-6	Ethyl acetate	1,700 ppm
123-86-4	n-Butyl acetate	200 ppm
77-58-7	dibutyltin dilaurate	8 mg/m³
822-06-0	hexamethylene-di-isocyanate	0.2 ppm
· PAC-3:		·
28182-81-2	Hexamethylene diisocyanate, oligomers	510 mg/m³
141-78-6	Ethyl acetate	10000** ppm
123-86-4	n-Butyl acetate	3000* ppm
77-58-7	dibutyltin dilaurate	48 mg/m³
822-06-0	hexamethylene-di-isocyanate	3 ррт

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

141-	141-78-6 Ethyl acetate		
PEL	Long-term value: 1400 mg/m³, 400 ppm		
REL	Long-term value: 1400 mg/m³, 400 ppm		
TLV	Long-term value: 400 ppm		
	(O-utd		

(Contd. on page 5)



acc. to OSHA HCS

Printing date 06/09/2023 Reviewed on 06/09/2023

Trade name: Mipa 2K-HS-Härter HS 5

(Contd. of page 4)

123-86-4 n-Butyl acetate

PEL Long-term value: 710 mg/m³, 150 ppm REL Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm

TLV Short-term value: 150 ppm Long-term value: 50 ppm

77-58-7 dibutyltin dilaurate

PEL Long-term value: 0.1 mg/m³

as Sn

REL Long-term value: 0.1 mg/m³

as Sn, Skin

TLV Short-term value: 0.2 mg/m³

Long-term value: 0.1 mg/m³

as Sn; A4; Skin

· Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Breathing equipment:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

(Contd. of page 5)



Safety Data Sheet acc. to OSHA HCS

Reviewed on 06/09/2023 Printing date 06/09/2023

Trade name: Mipa 2K-HS-Härter HS 5

· Eye protection:



Tightly sealed goggles

Physical and chemical proper	ties
Information on basic physical and c General Information	hemical properties
Appearance: Form:	Fluid
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	77-78 °C (170.6-172.4 °F)
Flash point:	-4 °C (24.8 °F) (DIN 53213)
Flammability (solid, gaseous):	Highly flammable.
Auto igniting:	370 °C (698 °F) (DIN 51794)
Decomposition temperature:	Not determined.
lgnition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explo air/vapor mixtures are possible.
Explosion limits:	2.4.10/
Lower:	2.1 Vol % 11.5 Vol %
Upper:	
Vapor pressure at 20 °C (68 °F):	97 hPa (72.8 mm Hg)
Vapor pressure at 50 °C (122 °F):	360 hPa (270 mm Hg)
Density at 20 °C (68 °F):	1.026 g/cm³ (8.562 lbs/gal) (DIN 53217)
Relative density Vapor density	Not determined. Not determined
Evaporation rate	Not determined. Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	r): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C (68 °F):	10-15 s (DIN 53211/4)
Solvent content:	
VOC content:	45.47 %
	467 g/l / 3.9 lb/gal



acc. to OSHA HCS

Printing date 06/09/2023 Reviewed on 06/09/2023

Trade name: Mipa 2K-HS-Härter HS 5

(Contd. of page 6)

· Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

28182-81-2 Hexamethylene diisocyanate, oligomers

Inhalative LC50/4 h 1.5 mg/l (rat)

- Primary irritant effect:
- · on the skin: No irritant effect.
- on the eye: Irritating effect.
- · Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Contd. on page 8)



acc. to OSHA HCS

Reviewed on 06/09/2023 Printing date 06/09/2023

Trade name: Mipa 2K-HS-Härter HS 5

(Contd. of page 7)

- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

	_	port in	_	4.0
9 /	Irone	nort in	tormo	tion
14	Halls			

· UN-Number

· DOT, ADR, IMDG, IATA UN1263

· UN proper shipping name

·DOT

Paint related material

UN1263 PAINT RELATED MATERIAL · ADR

· IMDG, IATA PAINT RELATED MATERIAL

- · Transport hazard class(es)
- · DOT



· Class 3 Flammable liquids

· Label

· ADR



· Class 3 (F1) Flammable liquids

· Label

· IMDG, IATA



· Class 3 Flammable liquids

· Label

(Contd. on page 9)



acc. to OSHA HCS

Printing date 06/09/2023 Reviewed on 06/09/2023

Trade name: Mipa 2K-HS-Härter HS 5

	(Contd. of page
· Packing group · DOT, ADR, IMDG, IATA	II
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	<i>Warning: Flammable liquids</i> 33 <i>F-E,<u>S-E</u> B</i>
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
· ADR · Limited quantities (LQ)	5L
· IMDG · Limited quantities (LQ)	5L
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

· Section	355 (ex	tremelv	hazardous	substances):

None of the ingredient is listed.

Section 313 (Specific toxic chemical listings):

822-06-0 hexamethylene-di-isocyanate

· Hazardous Air Pollutants

822-06-0 hexamethylene-di-isocyanate

Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

TLV (Threshold Limit Value)

77-58-7 dibutyltin dilaurate A4 ≥0.1-<1%

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

(Contd. on page 10)



acc. to OSHA HCS

Reviewed on 06/09/2023 Printing date 06/09/2023

Trade name: Mipa 2K-HS-Härter HS 5

(Contd. of page 9)

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labeling:

Hexamethylene diisocyanate, oligomers

dibutyltin dilaurate

Ethyl acetate

n-Butyl acetate

· Hazard statements

H225 Highly flammable liquid and vapor.

H332 Harmful if inhaled.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction. H360 May damage fertility or the unborn child.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

· National regulations:

· Additional classification according to Decree on Hazardous Materials:

Class	Share in %
1	<1
NK	25-50

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Contact:

· Date of preparation / last revision 06/09/2023

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 11)



acc. to OSHA HCS

Reviewed on 06/09/2023 Printing date 06/09/2023

Trade name: Mipa 2K-HS-Härter HS 5

(Contd. of page 10)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, ÉU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 2: Flammable liquids - Category 2 Acute Toxicity - Inhalation 4: Acute toxicity - Category 4

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A Sensitization - Respiratory 1: Respiratory sensitisation – Category 1

Sensitization - Skin 1: Skin sensitisation - Category 1

Toxic to Reproduction 1B: Reproductive toxicity – Category 1B Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

* * Data compared to the previous version altered.

USA