

1 Identification

- **Product identifier**
 - **Trade name:** *Mipa 2K-HS-Klarlack CCD*
 - **Application of the substance / the mixture** *Clear coating material, Varnish*
 - **Details of the supplier of the safety data sheet**
 - **Manufacturer/Supplier:**
MIPA SE
Am Oberen Moos 1
D-84051 Essenbach
Tel.: +49(0)8703-922-0
Fax.: +49(0)8703-922-100
e-mail: sdb-registratur@mipa-paints.com
www.mipa-paints.com
 - **Emergency telephone number:**
International: 011 49(0)700 24112112 (MIP)
US: +1 872 5888271 (MIP)
US Emergency Telephone Number (for transportation incidents only): 1-800-535-5053 (Infotrac)
- Fleetwood Products Inc.
13 American Way Suite 15
USA - NJ 08884 Spotswood
Tel.: +1 7324169590
e.mail: fleet089@hotmail.com*

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS08 Health hazard

Toxic to Reproduction 2

H361 Suspected of damaging fertility or the unborn child.



GHS07

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02

GHS07

GHS08

- **Signal word** *Warning*

- **Hazard-determining components of labeling:**

n-Butyl acetate

Reaction mass of pentamethyl-piperidyl sebacate

Hydrocarbons, C9, aromatics

2-Methoxy-1-methylethyl acetate

Trade name: Mipa 2K-HS-Klarlack CCD

(Contd. of page 1)

Hazard statements

- H226 Flammable liquid and vapor.
- H317 May cause an allergic skin reaction.
- H361 Suspected of damaging fertility or the unborn child.
- H336 May cause drowsiness or dizziness.

Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312 Call a poison center/doctor if you feel unwell.

Classification system:

NFPA ratings (scale 0 - 4)



Health = 0
Fire = 3
Reactivity = 0

HMIS-ratings (scale 0 - 4)



HEALTH 0 Health = 0
FIRE 3 Fire = 3
REACTIVITY 0 Reactivity = 0

Other hazards

Results of PBT and vPvB assessment

- PBT:** Not applicable.
- vPvB:** Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

| | | |
|------------|---|----------|
| 123-86-4 | n-Butyl acetate | 25-50% |
| 64742-95-6 | Hydrocarbons, C9, aromatics | 5-<10% |
| 1330-20-7 | Xylene | 2.5-<5% |
| 108-65-6 | 2-Methoxy-1-methylethyl acetate | 2.5-<10% |
| 26761-45-5 | 2,3-Epoxypropyl neodecanoate | ≥0.1-<1% |
| | Reaction mass of pentamethyl-piperidyl sebacate | ≥0.1-<1% |

4 First-aid measures

Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately rinse with water.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

Trade name: Mipa 2K-HS-Klarlack CCD

(Contd. of page 2)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

| | | |
|-----------|--------------------------------------|-----------------------|
| 123-86-4 | n-Butyl acetate | 5 ppm |
| 7631-86-9 | Silicon dioxide, chemically prepared | 18 mg/m ³ |
| 1330-20-7 | Xylene | 130 ppm |
| 108-65-6 | 2-Methoxy-1-methylethyl acetate | 50 ppm |
| 100-41-4 | Ethylbenzene | 33 ppm |
| 104-76-7 | 2-Ethyl-1-hexanol | 0.1 ppm |
| 9002-88-4 | Polyethylene low density | 16 mg/m ³ |
| 868-77-9 | 2-Hydroxyethyl methacrylate | 1.9 mg/m ³ |
| 67-68-5 | dimethyl sulfoxide | 150 ppm |
| 77-58-7 | dibutyltin dilaurate | 1.1 mg/m ³ |
| 556-67-2 | octamethylcyclotetrasiloxane | 30 ppm |
| 7447-41-8 | lithium chloride | 2.3 mg/m ³ |
| 540-97-6 | Dodecamethylcyclohexasiloxane | 150 mg/m ³ |

· **PAC-2:**

| | | |
|-----------|--------------------------------------|-----------------------|
| 123-86-4 | n-Butyl acetate | 200 ppm |
| 7631-86-9 | Silicon dioxide, chemically prepared | 740 mg/m ³ |
| 1330-20-7 | Xylene | 920* ppm |
| 108-65-6 | 2-Methoxy-1-methylethyl acetate | 1,000 ppm |

(Contd. on page 4)

Trade name: Mipa 2K-HS-Klarlack CCD

| | | (Contd. of page 3) |
|-----------|-------------------------------|-------------------------|
| 100-41-4 | Ethylbenzene | 1100* ppm |
| 104-76-7 | 2-Ethyl-1-hexanol | 100 ppm |
| 9002-88-4 | Polyethylene low density | 170 mg/m ³ |
| 868-77-9 | 2-Hydroxyethyl methacrylate | 21 mg/m ³ |
| 67-68-5 | dimethyl sulfoxide | 290 ppm |
| 77-58-7 | dibutyltin dilaurate | 8 mg/m ³ |
| 556-67-2 | octamethylcyclotetrasiloxane | 68 ppm |
| 7447-41-8 | lithium chloride | 25 mg/m ³ |
| 540-97-6 | Dodecamethylcyclohexasiloxane | 1,700 mg/m ³ |

PAC-3:

| | | |
|-----------|--------------------------------------|-------------------------|
| 123-86-4 | n-Butyl acetate | 3000* ppm |
| 7631-86-9 | Silicon dioxide, chemically prepared | 4,500 mg/m ³ |
| 1330-20-7 | Xylene | 2500* ppm |
| 108-65-6 | 2-Methoxy-1-methylethyl acetate | 5000* ppm |
| 100-41-4 | Ethylbenzene | 1800* ppm |
| 104-76-7 | 2-Ethyl-1-hexanol | 200 ppm |
| 9002-88-4 | Polyethylene low density | 1,000 mg/m ³ |
| 868-77-9 | 2-Hydroxyethyl methacrylate | 1,000 mg/m ³ |
| 67-68-5 | dimethyl sulfoxide | 1,800 ppm |
| 77-58-7 | dibutyltin dilaurate | 48 mg/m ³ |
| 556-67-2 | octamethylcyclotetrasiloxane | 130 ppm |
| 7447-41-8 | lithium chloride | 150 mg/m ³ |
| 540-97-6 | Dodecamethylcyclohexasiloxane | 9,900 mg/m ³ |

7 Handling and storage

· Handling:
· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities
· Storage:

- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 5)

Trade name: Mipa 2K-HS-Klarlack CCD

(Contd. of page 4)

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

123-86-4 n-Butyl acetate

| | |
|-----|---|
| PEL | Long-term value: 710 mg/m ³ , 150 ppm |
| REL | Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm |
| TLV | Short-term value: 150 ppm Long-term value: 50 ppm |

1330-20-7 Xylene

| | |
|-----|---|
| PEL | Long-term value: 435 mg/m ³ , 100 ppm |
| REL | Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm |
| TLV | Long-term value: 20 ppm BEI, A4 |

108-65-6 2-Methoxy-1-methylethyl acetate

| | |
|------|-------------------------|
| WEEL | Long-term value: 50 ppm |
|------|-------------------------|

· **Ingredients with biological limit values:**

1330-20-7 Xylene

| | |
|-----|--|
| BEI | 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids |
|-----|--|

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.

· **Breathing equipment:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

Trade name: Mipa 2K-HS-Klarlack CCD

(Contd. of page 5)

- **Breakthrough time of glove material**
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

| | |
|--------------------------|------------------------------------|
| · Form: | Fluid |
| · Color: | According to product specification |
| · Odor: | Characteristic |
| · Odor threshold: | Not determined. |

· **pH-value:** Not determined.

· Change in condition

| | |
|---------------------------------------|-----------------------------|
| · Melting point/Melting range: | Undetermined. |
| · Boiling point/Boiling range: | 124-128 °C (255.2-262.4 °F) |

· **Flash point:** 27 °C (80.6 °F) (DIN EN ISO 1523:2002)

· **Flammability (solid, gaseous):** Flammable.

· **Ignition temperature:** 370 °C (698 °F) (DIN 51794)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

| | |
|-----------------|-----------|
| · Lower: | 1.2 Vol % |
| · Upper: | 7.5 Vol % |

· **Vapor pressure at 20 °C (68 °F):** 10.7 hPa (8 mm Hg)

· **Density at 20 °C (68 °F):** 1.07 g/cm³ (8.929 lbs/gal) (DIN EN ISO 2811-1)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· Solubility in / Miscibility with

· **Water:** Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· Viscosity:

| | |
|--------------------------------------|-------------------------|
| · Dynamic: | Not determined. |
| · Kinematic at 20 °C (68 °F): | 150-170 s (DIN 53211/4) |

· Solvent content:

| | |
|-----------------------|----------------------|
| · VOC content: | 47.41 % |
| | 507 g/l / 4.2 lb/gal |

(Contd. on page 7)

Trade name: Mipa 2K-HS-Klarlack CCD

(Contd. of page 6)

Solids content (weight-%): 52.6 %

Other information No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

| | | |
|-----------|--------------------------------------|----|
| 7631-86-9 | Silicon dioxide, chemically prepared | 3 |
| 1330-20-7 | Xylene | 3 |
| 100-41-4 | Ethylbenzene | 2B |
| 9002-88-4 | Polyethylene low density | 3 |

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 8)

Trade name: Mipa 2K-HS-Klarlack CCD

(Contd. of page 7)

- *Danger to drinking water if even small quantities leak into the ground.*
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:**
Packagings that cannot be cleansed are to be disposed of in the same manner as the product.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1263
- **UN proper shipping name**
- **DOT** Paint
- **ADR** UN1263 PAINT
- **IMDG, IATA** PAINT
- **Transport hazard class(es)**
- **DOT**
- A red diamond-shaped hazard label with a flame icon and the text "FLAMMABLE LIQUID" and the number "3" at the bottom.
- **Class** 3 Flammable liquids
- **Label** 3
- **ADR**
- A red diamond-shaped hazard label with a flame icon and the number "3" at the bottom.
- **Class** 3 (F1) Flammable liquids
- **Label** 3
- **IMDG, IATA**
- A red diamond-shaped hazard label with a flame icon and the number "3" at the bottom.
- **Class** 3 Flammable liquids
- **Label** 3
- **Packing group**
- **DOT, ADR, IMDG, IATA** III

(Contd. on page 9)

Trade name: Mipa 2K-HS-Klarlack CCD

(Contd. of page 8)

| | |
|--|----------------------------|
| · Environmental hazards: | Not applicable. |
| · Special precautions for user | Warning: Flammable liquids |
| · Hazard identification number (Kemler code): | 30 |
| · EMS Number: | F-E, S-E |
| · Stowage Category | A |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · ADR | |
| · Limited quantities (LQ) | 5L |
| · Remarks: | ≤ 450 l: 2.2.3.1.5 ADR |
| · IMDG | |
| · Limited quantities (LQ) | 5L |
| · Remarks: | ≤ 5 l: 2.2.3.1.5 IMDG |
| · UN "Model Regulation": | UN 1263 PAINT, 3, III |

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7 Xylene

100-41-4 Ethylbenzene

· **Hazardous Air Pollutants**

1330-20-7 Xylene

100-41-4 Ethylbenzene

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-41-4 Ethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogeny categories**

· **EPA (Environmental Protection Agency)**

1330-20-7 Xylene

I

100-41-4 Ethylbenzene

D

· **TLV (Threshold Limit Value)**

1330-20-7 Xylene

A4 2.5-<5%

(Contd. on page 10)

Trade name: Mipa 2K-HS-Klarlack CCD

(Contd. of page 9)

| | | | |
|----------|----------------------|----|-------|
| 100-41-4 | Ethylbenzene | A3 | <1% |
| 77-58-7 | dibutyltin dilaurate | A4 | <0.1% |

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Warning

· **Hazard-determining components of labeling:**

n-Butyl acetate

Reaction mass of pentamethyl-piperidyl sebacate

Hydrocarbons, C9, aromatics

2-Methoxy-1-methylethyl acetate

· **Hazard statements**

H226 Flammable liquid and vapor.

H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a poison center/doctor if you feel unwell.

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials:**

| Class | Share in % |
|-------|------------|
| NK | 25-50 |

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Contact:**

· **Date of preparation / last revision** 03/01/2023

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

(Contd. on page 11)

Trade name: Mipa 2K-HS-Klarlack CCD

(Contd. of page 10)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEL: Biological Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3

Sensitization - Skin 1: Skin sensitisation – Category 1

Toxic to Reproduction 2: Reproductive toxicity – Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

· * **Data compared to the previous version altered.**

USA