

1 Identification

- **Product identifier**
- **Trade name:** *Mipa 2K-HS-NiN-Füller F 37*
- **Application of the substance / the mixture** *Filler*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MIPA SE
Am Oberen Moos 1
D-84051 Essenbach
Tel.: +49(0)8703-922-0
Fax.: +49(0)8703-922-100
e-mail: sdb-registratur@mipa-paints.com
www.mipa-paints.com
- **Emergency telephone number:**
International: 011 49(0)700 24112112 (MIP)
US: +1 872 5888271 (MIP)
US Emergency Telephone Number (for transportation incidents only): 1-800-535-5053 (Infotrac)

Mipa USA Inc.
13 American Way Suite 15
USA - NJ 08884 Spotswood
Tel.: +1 7324169590
e.mail: info@mipa-usa.com

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS08 Health hazard

Toxic to Reproduction 1B

H360 May damage fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure 2

H373 May cause damage to the hearing organs through prolonged or repeated exposure.



GHS07

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** *Danger*

- **Hazard-determining components of labeling:**

Reaction mass of ethylbenzene and xylene

Dibutyltin dilaurate

Pentaerythritol tetrakis(3-mercaptopropionate)

- **Hazard statements**

H226 Flammable liquid and vapor.

H317 May cause an allergic skin reaction.

Printing date 01/13/2026

Reviewed on 01/13/2026

Trade name: Mipa 2K-HS-NiN-Füller F 37

(Contd. of page 1)

H360 May damage fertility or the unborn child.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P363 Wash contaminated clothing before reuse.

P403+P235 Store in a well-ventilated place. Keep cool.

Classification system:

NFPA ratings (scale 0 - 4)



Health = 0

Fire = 3

Reactivity = 0

HMIS-ratings (scale 0 - 4)



Health = 0

Fire = 3

Reactivity = 0

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

123-86-4	n-Butyl acetate	<15%
	Reaction mass of ethylbenzene and xylene	2.5-<10%
108-65-6	2-Methoxy-1-methylethyl acetate	2.5-<10%
112-07-2	2-Butoxyethyl acetate	1-<2.5%
77-58-7	Dibutyltin dilaurate	≥0.1-<1%
7575-23-7	Pentaerythritol tetrakis(3-mercaptopropionate)	≥0.1-<1%

4 First-aid measures

Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately rinse with water.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: If symptoms persist consult doctor.

Information for doctor:

Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)

Trade name: Mipa 2K-HS-NiN-Füller F 37

(Contd. of page 2)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

123-86-4	n-Butyl acetate	5 ppm
108-65-6	2-Methoxy-1-methylethyl acetate	50 ppm
112-07-2	2-Butoxyethyl acetate	15 ppm
77-58-7	Dibutyltin dilaurate	1.1 mg/m ³

· PAC-2:

123-86-4	n-Butyl acetate	200 ppm
108-65-6	2-Methoxy-1-methylethyl acetate	1,000 ppm
112-07-2	2-Butoxyethyl acetate	35 ppm
77-58-7	Dibutyltin dilaurate	3.8 mg/m ³

· PAC-3:

123-86-4	n-Butyl acetate	3000* ppm
108-65-6	2-Methoxy-1-methylethyl acetate	5000* ppm
112-07-2	2-Butoxyethyl acetate	210 ppm
77-58-7	Dibutyltin dilaurate	23 mg/m ³

USA

(Contd. on page 4)

Trade name: Mipa 2K-HS-NiN-Füller F 37

(Contd. of page 3)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

123-86-4 n-Butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm

108-65-6 2-Methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

112-07-2 2-Butoxyethyl acetate

REL	Long-term value: 33 mg/m ³ , 5 ppm
TLV	Long-term value: 131 mg/m ³ , 20 ppm A3

77-58-7 Dibutyltin dilaurate

PEL	Long-term value: 0.1 mg/m ³ as Sn
REL	Long-term value: 0.1 mg/m ³ as Sn, Skin
TLV	Short-term value: 0.2 mg/m ³ Long-term value: 0.1 mg/m ³ as Sn; A4; Skin

- **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 5)

Trade name: Mipa 2K-HS-NiN-Füller F 37

(Contd. of page 4)

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
- **Breathing equipment:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Fluid
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.
- **pH-value:** Not determined.
- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	124-128 °C (255.2-262.4 °F)
- **Flash point:** 24 °C (75.2 °F) (DIN EN ISO 1523:2002)
- **Flammability:** Flammable.
- **Auto igniting:** 390 °C (734 °F) (DIN 51794)
- **Decomposition temperature:** Not determined.

(Contd. on page 6)

Trade name: Mipa 2K-HS-NiN-Füller F 37

(Contd. of page 5)

· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	8.5 Vol %
· Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
· Vapor pressure at 50 °C (122 °F):	55 hPa (41.3 mm Hg)
· Density at 20 °C (68 °F):	1.476 g/cm ³ (12.317 lbs/gal) (DIN EN ISO 2811-1)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C (68 °F):	>60 s (DIN 53211/4)
· Solvent content:	
VOC content:	26.92 % 397 g/l / 3.3 lb/gal
Solids content (weight-%):	73.1 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
123-86-4 n-Butyl acetate		
Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Reaction mass of ethylbenzene and xylene		
Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	15,400 mg/kg (rat)

(Contd. on page 7)

Printing date 01/13/2026

Reviewed on 01/13/2026

Trade name: Mipa 2K-HS-NiN-Füller F 37

(Contd. of page 6)

Inhalative	LC50/4 h	17.6 mg/l (rat)
108-65-6 2-Methoxy-1-methylethyl acetate		
Oral	LD50	8,532 mg/kg (rat)
112-07-2 2-Butoxyethyl acetate		
Oral	LD50	1,880 mg/kg (rat)
Dermal	LD50	1,480 mg/kg (rabbit)
7575-23-7 Pentaerythritol tetrakis(3-mercaptopropionate)		
Oral	LD50	1,000-2,000 mg/kg (rat)

· **Primary irritant effect:**

· **on the skin:** No irritant effect.

· **on the eye:** No irritating effect.

· **Sensitization:** Sensitization possible through skin contact.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

13463-67-7	Titanium dioxide	2B
14807-96-6	Talc	2A

· **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO ₂)	K
584-84-9	4-methyl-m-phenylene diisocyanate	R

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

-USA-

(Contd. on page 8)

Trade name: Mipa 2K-HS-NiN-Füller F 37

(Contd. of page 7)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:**
Packagings that cannot be cleansed are to be disposed of in the same manner as the product.

14 Transport information

· UN-Number	UN1263
· DOT, ADR, IMDG, IATA	
· UN proper shipping name	Paint
· DOT	UN1263 PAINT, ENVIRONMENTALLY HAZARDOUS
· ADR	PAINT (Trizinc bis(orthophosphate), Polythiols), MARINE POLLUTANT
· IMDG	PAINT
· IATA	
· Transport hazard class(es)	
· DOT	
	
· Class	3 Flammable liquids
· Label	3
· ADR	
	
· Class	3 (F1) Flammable liquids
· Label	3
· IMDG	
	
· Class	3 Flammable liquids
· Label	3
· IATA	
	
· Class	3 Flammable liquids

(Contd. on page 9)

Printing date 01/13/2026

Reviewed on 01/13/2026

Trade name: Mipa 2K-HS-NiN-Füller F 37

(Contd. of page 8)

· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	Product contains environmentally hazardous substances: Dibutyltin dilaurate
· Marine pollutant:	Yes (DOT) Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E, S-E
· Segregation groups	(SGG1) Acids
· Stowage Category	A
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Remarks:	Special marking with the symbol (fish and tree).
· ADR	
· Limited quantities (LQ)	5L
· Remarks:	≤ 5 l: 2.2.3.1.5 ADR
· IMDG	
· Limited quantities (LQ)	5L
· Remarks:	≤ 5 l: 2.3.2.5 IMDG
· UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

584-84-9 | 4-methyl-m-phenylene diisocyanate

· **Section 313 (Specific toxic chemical listings):**

112-07-2 | 2-Butoxyethyl acetate

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

Reaction mass of ethylbenzene and xylene

13463-67-7 | Titanium dioxide

14808-60-7 | Quartz (SiO₂)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

(Contd. on page 10)

Printing date 01/13/2026

Reviewed on 01/13/2026

Trade name: Mipa 2K-HS-NiN-Füller F 37

(Contd. of page 9)

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3 Toluene

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value)**

112-07-2	2-Butoxyethyl acetate	A3	1-<2.5%
77-58-7	Dibutyltin dilaurate	A4	≥0.1-<1%

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	Titanium dioxide
14808-60-7	Quartz (SiO ₂)
584-84-9	4-methyl-m-phenylene diisocyanate

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word Danger**

· **Hazard-determining components of labeling:**

Reaction mass of ethylbenzene and xylene

Dibutyltin dilaurate

Pentaerythritol tetrakis(3-mercaptopropionate)

· **Hazard statements**

H226 Flammable liquid and vapor.

H317 May cause an allergic skin reaction.

H360 May damage fertility or the unborn child.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P363 Wash contaminated clothing before reuse.

P403+P235 Store in a well-ventilated place. Keep cool.

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials:**

Class	Share in %
I	<1
NK	25-50

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

USA

(Contd. on page 11)

Printing date 01/13/2026

Reviewed on 01/13/2026

Trade name: Mipa 2K-HS-NiN-Füller F 37

(Contd. of page 10)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Contact:**

· **Date of preparation / last revision** 01/13/2026 / 5

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3

Sensitization - Skin 1: Skin sensitisation – Category 1

Toxic to Reproduction 1B: Reproductive toxicity – Category 1B

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2

· *** Data compared to the previous version altered.**

USA