

1 Identification

- · Product identifier
- · Trade name: Mipa 2K-Multifiller
- · Application of the substance / the mixture Filler
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: MIPA SE Am Oberen Moos 1 D-84051 Essenbach Tel.: +49(0)8703-922-0 Fax.: +49(0)8703-922-100 e-mail: sdb-registratur@mipa-paints.com www.mipa-paints.com
- Emergency telephone number: International: 011 49(0)700 24112112 (MIP) US: +1 872 5888271 (MIP)

Fleetwood Products Inc. 13 American Way Suite 15 USA - NJ 08884 Spotswood Tel.: +1 7324169590 e.mail: fleet089@hotmail.com

Reviewed on 10/02/2024

US Emergency Telephone Number (for transportation incidents only): 1-800-535-5053 (Infotrac)

Safety Data Sheet

acc. to OSHA HCS

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 3

GHS08 Health hazard

Toxic to Reproduction 1B Specific Target Organ Toxicity - Repeated Exposure 2

H360 May damage fertility or the unborn child. H373 May cause damage to the hearing organs through prolonged or repeated exposure.

H226 Flammable liquid and vapor.

GHS07

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling: **Xylene** Dibutyltin dilaurate Ethylbenzene · Hazard statements H226 Flammable liquid and vapor. H317 May cause an allergic skin reaction.

(Contd. on page 2)



Trade name: Mipa 2K-Multifiller

Reviewed on 10/02/2024

	(Contd. of page 1)
, , ,	ge fertility or the unborn child.
	damage to the hearing organs through prolonged or repeated exposure.
Precautionary s	
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P35	3 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P363	Wash contaminated clothing before reuse.
P403+P235	Store in a well-ventilated place. Keep cool.
Classification sy	
· NFPA ratings (s	
0 0 Fire Rea	= 3 $ctivity = 0$
· HMIS-ratings (so	cale 0 - 4)
FIRE 3 Fire	alth = 0 e = 3 activity = 0
· Other hazards	
•	and vPvB assessment
• PBT: Not applica	
• vPvB: Not applied	

Safety Data Sheet

acc. to OSHA HCS

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerou:	· Dangerous components:	
	n-Butyl acetate	<15%
1330-20-7	Xylene	5-<10%
108-65-6	2-Methoxy-1-methylethyl acetate	<2.5%
	Ethylbenzene	<2.5%
77-58-7	Dibutyltin dilaurate	<i>≥</i> 0.1-<1%

4 First-aid measures

· Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • **After swallowing:** If symptoms persist consult doctor.

- Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.

(Contd. on page 3)

- USA



Trade name: Mipa 2K-Multifiller

Reviewed on 10/02/2024

(Contd. of page 2)

• Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Safety Data Sheet

acc. to OSHA HCS

• For safety reasons unsuitable extinguishing agents: Water with full jet

• Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.

- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

Mount resp Wear prote • Environme • Methods a Absorb with Dispose co Ensure ade • Reference See Sectio See Sectio See Sectio	brecautions, protective equipment and emergency procedures biratory protective device. bective equipment. Keep unprotected persons away. bective equipment. Keep unprotected persons away. bental precautions: Do not allow to enter sewers/ surface or ground water. and material for containment and cleaning up: be liquid-binding material (sand, diatomite, acid binders, universal binders, s bintaminated material as waste according to section 13. bequate ventilation. to other sections n 7 for information on safe handling. n 8 for information on personal protection equipment. n 13 for disposal information. Action Criteria for Chemicals	awdust).
· PAC-1:		
123-86-4	n-Butyl acetate	5 ppm
1330-20-7	Xylene	130 ppm
108-65-6	2-Methoxy-1-methylethyl acetate	50 ppm
100-41-4	Ethylbenzene	33 ppm
77-58-7	DibutyItin dilaurate	1.1 mg/m³
· PAC-2:		
123-86-4	n-Butyl acetate	200 ppm
1330-20-7	Xylene	920* ppm
108-65-6	2-Methoxy-1-methylethyl acetate	1,000 ppm
100-41-4	Ethylbenzene	1100* ppm
77-58-7	DibutyItin dilaurate	8 mg/m³
· PAC-3:		
123-86-4	n-Butyl acetate	3000* ppm
1330-20-7	Xylene	2500* ppm
108-65-6	2-Methoxy-1-methylethyl acetate	5000* ppm
100-41-4	Ethylbenzene	1800* ppm
77-58-7	DibutyItin dilaurate	48 mg/m³
		US/

(Contd. on page 4)



Trade name: Mipa 2K-Multifiller

Reviewed on 10/02/2024

(Contd. of page 3)

7 Handling and storage

· Handling:

- Precautions for safe handling
 Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.

Safety Data Sheet

acc. to OSHA HCS

- Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

123-8	6-4 n-Butyl acetate	
PEL	Long-term value: 710 mg/m³, 150 ppm	
REL	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm	
TLV	Short-term value: 150 ppm Long-term value: 50 ppm	
1330-2	20-7 Xylene	
PEL	Long-term value: 435 mg/m³, 100 ppm	
REL	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm	
TLV	Long-term value: 20 ppm BEI, A4	
108-6	5-6 2-Methoxy-1-methylethyl acetate	
WEEL	Long-term value: 50 ppm	
100-4	1-4 Ethylbenzene	
PEL	Long-term value: 435 mg/m³, 100 ppm	
REL	Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm	
TLV	Long-term value: 20 ppm OTO, BEI, A3	
77-58	-7 Dibutyltin dilaurate	
PEL	Long-term value: 0.1 mg/m³ as Sn	
		(Contd. on page



Trade name: Mipa 2K-Multifiller

Reviewed on 10/02/2024

REL	(Contd. of pa Long-term value: 0.1 mg/m ³ as Sn, Skin
TLV	Short-term value: 0.2 mg/m³ Long-term value: 0.1 mg/m³ as Sn; A4; Skin
Ingre	dients with biological limit values:
1330-	20-7 Xylene
۸ 7	l.5 g/g creatinine Medium: urine Fime: end of shift Parameter: Methylhippuric acids
100-4	1-4 Ethylbenzene
۸ 7).15 g/g creatinine Aedium: urine Fime: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)
Addit	ional information: The lists that were valid during the creation were used as basis.
Perso	sure controls onal protective equipment: ral protective and hygienic measures:

Safety Data Sheet

acc. to OSHA HCS

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.

Store protective clothing separately.

Breathing equipment:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Eye protection:



Tightly sealed goggles

(Contd. on page 6)

USA



Safety Data Sheet acc. to OSHA HCS

Reviewed on 10/02/2024

Trade name: Mipa 2K-Multifiller

(Contd. of page 5)

9 Physical and chemical proper	rties
 Information on basic physical and c General Information Appearance: 	hemical properties
Form:	Fluid
Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. 124-128 °C (255.2-262.4 °F)
· Flash point:	24 °C (75.2 °F) (DIN EN ISO 1523:2002)
· Flammability:	Flammable.
· Auto igniting:	>350 °C (>662 °F) (DIN 51794)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits: Lower: Upper:	1.2 Vol % 7.5 Vol %
 Vapor pressure at 20 °C (68 °F): Vapor pressure at 50 °C (122 °F): 	<15 hPa (<11.3 mm Hg) 55 hPa (41.3 mm Hg)
 Density at 20 °C (68 °F): Relative density Vapor density Evaporation rate 	1.608 g/cm³ (13.419 lbs/gal) (DIN EN ISO 2811-1) Not determined. Not determined. Not determined.
 Solubility in / Miscibility with Water: 	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	r): Not determined.
· Viscosity: Dynamic: Kinematic at 20 °C (68 °F):	Not determined. >60 s (ISO 6 mm)
• Solvent content: VOC content:	23.41 % 376 g/l / 3.1 lb/gal
Solids content (weight-%):	76.3 %
· Other information	No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

· Chemical stability

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 7)

⁻ USA

(Contd. of page 6)



Printing date 10/02/2024

Trade name: Mipa 2K-Multifiller

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Safety Data Sheet

acc. to OSHA HCS

Irritant

Carcinogenic categories

· IARC (Inter	national Agency for Research on Cancer)	
14807-96-6	Talc	3
1330-20-7	Xylene	3
13463-67-7	Titanium dioxide	2B
100-41-4	Ethylbenzene	2B
1333-86-4	Carbon black	2B
· NTP (Natio	nal Toxicology Program)	
14808-60-7	Quartz (SiO2)	K
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the	ingredients is listed.	

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

(Contd. on page 8)

USA

Reviewed on 10/02/2024



Safety Data Sheet acc. to OSHA HCS

Reviewed on 10/02/2024

Trade name: Mipa 2K-Multifiller

(Contd. of page 7)

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

UN-Number	104000
DOT, ADR, IMDG, IATA	UN1263
UN proper shipping name	5
DOT	Paint
ADR	UN1263 PAINT
IMDG, IATA	PAINT
Transport hazard class(es)	
DOT	
RAMMARE LOUD	
Class	3 Flammable liquids
Label	3
ADR	
Class Label	3 (F1) Flammable liquids 3
IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group DOT, ADR, IMDG, IATA	<i>III</i>
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code):	30
EMS Number:	F-E,S-E
Stowage Category	A



Safety Data Sheet acc. to OSHA HCS

Reviewed on 10/02/2024

Trade name: Mipa 2K-Multifiller

	(Contd. of page 8
 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	Not applicable.
Transport/Additional information:	
· ADR · Limited quantities (LQ) · Remarks:	5L ≤ 450 l: 2.2.3.1.5 ADR
· IMDG · Limited quantities (LQ) · Remarks:	5L ≤ 450 l: 2.3.2.5 IMDG-Code
UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 35	5 (extremely hazardous substances):		
None of the	ingredient is listed.		
· Section 31	3 (Specific toxic chemical listings):		
1330-20-7	Xylene		
100-41-4	Ethylbenzene		
·Hazardous	Air Pollutants		
1330-20-7	Xylene		
100-41-4	Ethylbenzene		
· Propositio	n 65		
[.] Chemicals	known to cause cancer:		
100-41-4 E	thylbenzene		
· Chemicals	known to cause reproductive toxicity for females:		
None of the	ingredients is listed.		
· Chemicals	known to cause reproductive toxicity for males:		
None of the	ingredients is listed.		
· Canceroge	enity categories		
-	ronmental Protection Agency)		
1330-20-7	Xylene		1
100-41-4	Ethylbenzene		D
TLV (Three	hold Limit Value)		
1330-20-7	Xylene	A4	5-<10%
	Ethylbenzene	A3	<2.5%
77-58-7	Dibutyltin dilaurate	A4	<i>≥</i> 0.1-<1%
· NIOSH-Ca	(National Institute for Occupational Safety and Health)		
13463-67-7	Titanium dioxide		
1333-86-4	Carbon black		
	Quartz (SiO2)		
• GHS label The produc	t is classified and labeled according to the Globally Harmonized System (S). d. on page 10)

Professional Coating Systems

Printing date 10/02/2024

Trade name: Mipa 2K-Multifiller

Reviewed on 10/02/2024

· Hazard pictogr	(Contd. of page 9)
GHS02 GHS0	7 GHS08
· Signal word Da	
-	
Xylene	ining components of labeling:
Dibutyltin dilaura	ate
Ethylbenzene	
· Hazard stateme	ents
H226 Flammabl	e liquid and vapor.
	e an allergic skin reaction.
H360 May dama	ge fertility or the unborn child.
	e damage to the hearing organs through prolonged or repeated exposure.
Precautionary	
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P301+P3	53 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P363	Wash contaminated clothing before reuse.
P403+P235	Store in a well-ventilated place. Keep cool.
· National regula	tions:
-	sification according to Decree on Hazardous Materials:
Class Share	

Safety Data Sheet

acc. to OSHA HCS

Class	Share in %
NK	10-25

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Contact: · Date of preparation / last revision 10/02/2024 / 28 · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 3: Flammable liquids – Category 3 (Contd. on page 11) USA



Reviewed on 10/02/2024

Trade name: Mipa 2K-Multifiller

(Contd. of page 10)

Sensitization - Skin 1: Skin sensitisation – Category 1 Toxic to Reproduction 1B: Reproductive toxicity – Category 1B Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2 • * **Data compared to the previous version altered.**

Safety Data Sheet acc. to OSHA HCS

USA