

1 Identification

- **Product identifier**
- **Trade name:** *Mipa BC-Additiv VDG-HV*
- **Application of the substance / the mixture** *Solvents*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MIPA SE
Am Oberen Moos 1
D-84051 Essenbach
Tel.: +49(0)8703-922-0
Fax.: +49(0)8703-922-100
e-mail: sdb-registratur@mipa-paints.com
www.mipa-paints.com
- **Emergency telephone number:**
International: 011 49(0)700 24112112 (MIP)
US: +1 872 5888271 (MIP)
US Emergency Telephone Number (for transportation incidents only): 1-800-535-5053 (Infotrac)

*Fleetwood Products Inc.
13 American Way Suite 15
USA - NJ 08884 Spotswood
Tel.: +1 7324169590
e.mail: fleet089@hotmail.com*

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

*Specific Target Organ Toxicity - Repeated Exposure 2
Aspiration Hazard 1*

*H373 May cause damage to the hearing organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.*



GHS07

*Skin Irritation 2
Eye Irritation 2A
Specific Target Organ Toxicity - Single Exposure 3*

*H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.*

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** *Danger*
- **Hazard-determining components of labeling:**
Xylene

Trade name: Mipa BC-Additiv VDG-HV

(Contd. of page 1)

n-Butyl acetate

Ethylbenzene

Ethyl acetate

Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P301+P310 If swallowed: Immediately call a poison center/doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

Classification system:

NFPA ratings (scale 0 - 4)



Health = 2

Fire = 3

Reactivity = 0

HMIS-ratings (scale 0 - 4)



Health = 2

Fire = 3

Reactivity = 0

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

1330-20-7	Xylene	25-50%
123-86-4	<i>n</i> -Butyl acetate	25-50%
141-78-6	Ethyl acetate	10-25%
100-41-4	Ethylbenzene	2.5-<10%
108-65-6	2-Methoxy-1-methylethyl acetate	2.5-<10%

4 First-aid measures

Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately rinse with water.

(Contd. on page 3)

Trade name: Mipa BC-Additiv VDG-HV

(Contd. of page 2)

- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Seek immediate medical advice.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

1330-20-7	Xylene	130 ppm
123-86-4	n-Butyl acetate	5 ppm
141-78-6	Ethyl acetate	1,200 ppm
100-41-4	Ethylbenzene	33 ppm
108-65-6	2-Methoxy-1-methylethyl acetate	50 ppm

· PAC-2:

1330-20-7	Xylene	920* ppm
123-86-4	n-Butyl acetate	200 ppm
141-78-6	Ethyl acetate	1,700 ppm
100-41-4	Ethylbenzene	1100* ppm
108-65-6	2-Methoxy-1-methylethyl acetate	1,000 ppm

· PAC-3:

1330-20-7	Xylene	2500* ppm
123-86-4	n-Butyl acetate	3000* ppm

(Contd. on page 4)

Printing date 11/19/2024

Reviewed on 11/19/2024

Trade name: Mipa BC-Additiv VDG-HV

141-78-6	Ethyl acetate	(Contd. of page 3) 10000** ppm
100-41-4	Ethylbenzene	1800* ppm
108-65-6	2-Methoxy-1-methylethyl acetate	5000* ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

1330-20-7 Xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm BEI, A4

123-86-4 n-Butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

141-78-6 Ethyl acetate

PEL	Long-term value: 1400 mg/m ³ , 400 ppm
REL	Long-term value: 1400 mg/m ³ , 400 ppm
TLV	Long-term value: 400 ppm

100-41-4 Ethylbenzene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
-----	--

(Contd. on page 5)

USA

Trade name: Mipa BC-Additiv VDG-HV

(Contd. of page 4)

REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm OTO, BEI, A3
108-65-6 2-Methoxy-1-methylethyl acetate	
WEEL	Long-term value: 50 ppm
Ingredients with biological limit values:	
1330-20-7 Xylene	
BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
100-41-4 Ethylbenzene	
BEI	0.15 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Breakthrough time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Printing date 11/19/2024

Reviewed on 11/19/2024

Trade name: Mipa BC-Additiv VDG-HV

(Contd. of page 5)

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Fluid

Color:

According to product specification

· **Odor:**

Characteristic

· **Odor threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

77-78 °C (170.6-172.4 °F)

· **Flash point:**

-4 °C (24.8 °F) (DIN 53213)

· **Flammability:**

Highly flammable.

· **Auto igniting:**

370 °C (698 °F) (DIN 51794)

· **Decomposition temperature:**

Not determined.

· **Ignition temperature:**

Product is not selfigniting.

· **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower:

1.1 Vol %

Upper:

11.5 Vol %

· **Vapor pressure at 20 °C (68 °F):**

97 hPa (72.8 mm Hg)

· **Vapor pressure at 50 °C (122 °F):**

360 hPa (270 mm Hg)

· **Density at 20 °C (68 °F):**

0.887 g/cm³ (7.402 lbs/gal) (DIN 53217)

· **Relative density**

Not determined.

· **Vapor density**

Not determined.

· **Evaporation rate**

Not determined.

· **Solubility in / Miscibility with**

Water:

Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic:

Not determined.

Kinematic at 20 °C (68 °F):

12-14 s (DIN 53211/4)

· **Solvent content:**

VOC content:

98.00 %

869 g/l / 7.3 lb/gal

Solids content (weight-%):

2.0 %

(Contd. on page 7)

Printing date 11/19/2024

Reviewed on 11/19/2024

Trade name: Mipa BC-Additiv VDG-HV

(Contd. of page 6)

Other information

No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

1330-20-7 Xylene

Oral	LD50	5,251 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	29 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	Xylene	3
100-41-4	Ethylbenzene	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 8)

USA

Printing date 11/19/2024

Reviewed on 11/19/2024

Trade name: Mipa BC-Additiv VDG-HV




(Contd. of page 7)

- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1263
- **UN proper shipping name**
- **DOT** Paint related material
- **ADR** UN1263 PAINT RELATED MATERIAL
- **IMDG, IATA** PAINT RELATED MATERIAL
- **Transport hazard class(es)**
- **DOT**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **ADR**
- 
- **Class** 3 (F1) Flammable liquids
- **Label** 3
- **IMDG, IATA**
- 
- **Class** 3 Flammable liquids
- **Label** 3

(Contd. on page 9)

Printing date 11/19/2024

Reviewed on 11/19/2024

Trade name: Mipa BC-Additiv VDG-HV

(Contd. of page 8)

· Packing group	
· DOT, ADR, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	33
· EMS Number:	F-E, S-E
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· IMDG	
· Limited quantities (LQ)	5L
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7 Xylene

100-41-4 Ethylbenzene

· **Hazardous Air Pollutants**

1330-20-7 Xylene

100-41-4 Ethylbenzene

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-41-4 Ethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Cancerogeny categories**

· **EPA (Environmental Protection Agency)**

1330-20-7 Xylene

100-41-4 Ethylbenzene

I

D

(Contd. on page 10)

USA

Printing date 11/19/2024

Reviewed on 11/19/2024

Trade name: Mipa BC-Additiv VDG-HV

(Contd. of page 9)

· **TLV (Threshold Limit Value)**

1330-20-7	Xylene	A4	25-50%
100-41-4	Ethylbenzene	A3	2.5-<10%

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Xylene
n-Butyl acetate
Ethylbenzene
Ethyl acetate

· **Hazard statements**

H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to the hearing organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

P301+P310 If swallowed: Immediately call a poison center/doctor.
P321 Specific treatment (see on this label).
P331 Do NOT induce vomiting.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P362+P364 Take off contaminated clothing and wash it before reuse.

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials:**

Class	Share in %
NK	50-100

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Contact:**

· **Date of preparation / last revision** 11/19/2024 / 40

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 11/19/2024

Reviewed on 11/19/2024

Trade name: Mipa BC-Additiv VDG-HV

(Contd. of page 10)

IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flammable Liquids 2: Flammable liquids – Category 2
Skin Irritation 2: Skin corrosion/irritation – Category 2
Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3
Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2
Aspiration Hazard 1: Aspiration hazard – Category 1
* **Data compared to the previous version altered.**

USA