Fleetwood Products Inc.

Tel.: +1 7324169590

13 American Way Suite 15

USA - NJ 08884 Spotswood

e.mail: fleet089@hotmail.com



# Safety Data Sheet

acc. to OSHA HCS

Printing date 03/02/2023 Reviewed on 03/02/2023

## 1 Identification

- · Product identifier
- · Trade name: Mipa BC-Verdünnung
- · Application of the substance / the mixture Thinner, Diluent
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49(0)8703-922-0 Fax.: +49(0)8703-922-100

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

Emergency telephone number:

International: 011 49(0)700 24112112 (MIP)

US: +1 872 5888271 (MIP)

US Emergency Telephone Number (for transportation incidents only): 1-800-535-5053 (Infotrac)

# 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Specific Target Organ Toxicity - Repeated

Exposure 2

Aspiration Hazard 1

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irritation 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling: n-Butyl acetate

(Contd. on page 2)



acc. to OSHA HCS

Printing date 03/02/2023 Reviewed on 03/02/2023

Trade name: Mipa BC-Verdünnung

(Contd. of page 1)

Hydrocarbons, C9, aromatics

Ethylbenzene Ethyl acetate

## Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

#### · Precautionary statements

P301+P310 If swallowed: Immediately call a poison center/doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2 Fire = 3 Reactivity = 0

## · HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 3 Reactivity = 0

- Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
123-86-4	n-Butyl acetate	50-100%
64742-95-6	Hydrocarbons, C9, aromatics	≤20%
1330-20-7	Xylene	5-<10%
	Ethyl acetate	2.5-<10%
100-41-4	Ethylbenzene	<2.5%

#### 4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.

(Contd. on page 3)



acc. to OSHA HCS

Printing date 03/02/2023 Reviewed on 03/02/2023

Trade name: Mipa BC-Verdünnung

(Contd. of page 2)

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Seek immediate medical advice.
- Information for doctor:
- $\cdot$  Most important symptoms and effects, both acute and delayed

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

## 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:		
123-86-4	n-Butyl acetate	5 ppm
1330-20-7	Xylene	130 ppm
141-78-6	Ethyl acetate	1,200 ppm
100-41-4	Ethylbenzene	33 ppm
PAC-2:		
123-86-4	n-Butyl acetate	200 ppm
1330-20-7	Xylene	920* ppm
141-78-6	Ethyl acetate	1,700 ppm
100-41-4	Ethylbenzene	1100* ppm
PAC-3:		
123-86-4	n-Butyl acetate	3000* ppm
1330-20-7	Xylene	2500* ppm
141-78-6	Ethyl acetate	10000** ppn
		(Contd. on page



acc. to OSHA HCS

Printing date 03/02/2023 Reviewed on 03/02/2023

Trade name: Mipa BC-Verdünnung

 (Contd. of page 3)

 100-41-4 Ethylbenzene
 1800\* ppm

## 7 Handling and storage

- Handling:
- · Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

123-8	86-4 n-Butyl acetate	
PEL	Long-term value: 710 mg/m³, 150 ppm	
REL	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm	
TLV	Short-term value: 150 ppm Long-term value: 50 ppm	
1330	-20-7 Xylene	
PEL	Long-term value: 435 mg/m³, 100 ppm	
REL	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm	
TLV	Long-term value: 20 ppm BEI, A4	
141-7	78-6 Ethyl acetate	
PEL	Long-term value: 1400 mg/m³, 400 ppm	
REL	Long-term value: 1400 mg/m³, 400 ppm	
TLV	Long-term value: 400 ppm	
100-4	41-4 Ethylbenzene	
PEL	Long-term value: 435 mg/m³, 100 ppm	
		(Contd. on page



acc. to OSHA HCS

Printing date 03/02/2023 Reviewed on 03/02/2023

Trade name: Mipa BC-Verdünnung

(Contd. of page 4)

REL Short-term value: 545 mg/m³, 125 ppm

Long-term value: 435 mg/m³, 100 ppm

TLV Long-term value: 20 ppm

OTO, BEI, A3

#### Ingredients with biological limit values:

## 1330-20-7 Xylene

BEI 1.5 g/g creatinine

Medium: urine Time: end of shift

Parameter: Methylhippuric acids

#### 100-41-4 Ethylbenzene

BEI 0.15 g/g creatinine

Medium: urine

Time: end of shift at end of workweek

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

#### · Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

## · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

(Contd. of page 5)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 03/02/2023 Reviewed on 03/02/2023

Trade name: Mipa BC-Verdünnung

· Eye protection:



Tightly sealed goggles

9 Physical	and ch	emical	pro	perties
------------	--------	--------	-----	---------

· General Information

· Appearance:

Form: Fluid

Color: According to product specification

Odor: Characteristic
 Odor threshold: Not determined.
 pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

**Boiling point/Boiling range:** 77-78 °C (170.6-172.4 °F)

• Flash point: 21 °C (69.8 °F) (DIN 53213)

· Flammability (solid, gaseous): Highly flammable.

• Ignition temperature: 370 °C (698 °F) (DIN 51794)

· **Decomposition temperature:** Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive

air/vapor mixtures are possible.

· Explosion limits:

**Lower:** 0.7 Vol % **Upper:** 7.5 Vol %

· Vapor pressure at 20 °C (68 °F): 97 hPa (72.8 mm Hg)

Density at 20 °C (68 °F): 0.879 g/cm³ (7.335 lbs/gal) (DIN 53217)

Relative density
 Vapor density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

**Dynamic:** Not determined.

**Kinematic at 20 °C (68 °F):** 10-15 s (DIN 53211/4)

· Solvent content:

VOC content: 100.00 %

879 g/l / 7.3 lb/gal

Solids content (weight-%): 0.0 %

(Contd. on page 7)



acc. to OSHA HCS

Printing date 03/02/2023 Reviewed on 03/02/2023

Trade name: Mipa BC-Verdünnung

(Contd. of page 6)

· Other information

No further relevant information available.

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide

# 11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:
--

#### 123-86-4 n-Butyl acetate

Oral LD50 13,100 mg/kg (rat)
Dermal LD50 >5,000 mg/kg (rabbit)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

. Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
1330-20-7	Xylene	3
100-41-4	Ethylbenzene	2B
· NTP (National Toxicology Program)		

#### · NTP (National Toxicology Program)

None of the ingredients is listed.

## · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

# 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:

Water hazard class 2 (Self-assessment): hazardous for water

(Contd. on page 8)



acc. to OSHA HCS

Printing date 03/02/2023 Reviewed on 03/02/2023

Trade name: Mipa BC-Verdünnung

(Contd. of page 7)

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

Results of PBT and vPvB assessment

- · PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

· Class

· Label

· Packing group

· DOT, ADR, IMDG, IATA

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number DOT, ADR, IMDG, IATA	UN1263
UN proper shipping name	
DOT	Paint related material
ADR IMDG, IATA	UN1263 PAINT RELATED MATERIAL PAINT RELATED MATERIAL
	TAINT NELATED WATENIAL
Transport hazard class(es)	
DOT	
Class Label	3 Flammable liquids 3
ADR	
3	
Class	3 (F1) Flammable liquids
Label	3
IMDG, IATA	

3 Flammable liquids

3

11

(Contd. on page 9)



# Safety Data Sheet acc. to OSHA HCS

Printing date 03/02/2023 Reviewed on 03/02/2023

Trade name: Mipa BC-Verdünnung

	(Contd. of page
Environmental hazards: Marine pollutant:	No
Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	<i>Warning: Flammable liquids</i> 33 <i>F-E,<u>S-E</u> B</i>
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ)	5L
IMDG Limited quantities (LQ)	5L
UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, II

# 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Cara

· Sara		
· Section 355 (extremely hazardous substances):		
None of the ingredient is listed.		
· Section 313 (Specific toxic chemical listings):		
1330-20-7   Xylene		
100-41-4 Ethylbenzene		
· Hazardous Air Pollutants		
1330-20-7   Xylene		
100-41-4 Ethylbenzene		
Proposition 65		
· Chemicals known to cause cancer:		
100-41-4 Ethylbenzene		
· Chemicals known to cause reproductive toxicity for females:		
None of the ingredients is listed.		
. Chamicals known to cause reproductive toxicity for males:		

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)		
1330-20-7   Xylene	1	
100-41-4 Ethylbenzene	D	

1330-20-7   Xylene	A4	5-<10%
100-41-4 Ethylbenzene	<i>A3</i>	<2.5%

(Contd. on page 10)



acc. to OSHA HCS

Reviewed on 03/02/2023 Printing date 03/02/2023

Trade name: Mipa BC-Verdünnung

(Contd. of page 9)

#### NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

#### · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

#### Hazard pictograms







GHS02

GHS07

#### · Signal word Danger

### · Hazard-determining components of labeling:

n-Butyl acetate

Hydrocarbons, C9, aromatics

Ethylbenzene Ethyl acetate

#### Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

#### Precautionary statements

If swallowed: Immediately call a poison center/doctor. P301+P310

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

## · National regulations:

#### · Additional classification according to Decree on Hazardous Materials:

Class	Share in %	
NK	50-100	

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Contact:

· Date of preparation / last revision 03/02/2023

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 11)



acc. to OSHA HCS

Reviewed on 03/02/2023 Printing date 03/02/2023

Trade name: Mipa BC-Verdünnung

(Contd. of page 10)

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2 Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3
Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) - Category 2

Aspiration Hazard 1: Aspiration hazard - Category 1

\* Data compared to the previous version altered.

USA