

1 Identification

- **Product identifier**
- **Trade name: Mipa BC-Xirallic-Mischlack**
- **Application of the substance / the mixture Paint**
- **Details of the supplier of the safety data sheet**

- **Manufacturer/Supplier:**

MIPA SE
Am Oberen Moos 1
D-84051 Essenbach
Tel.: +49(0)8703-922-0
Fax.: +49(0)8703-922-100
e-mail: sdb-registratur@mipa-paints.com
www.mipa-paints.com

Fleetwood Products Inc.
13 American Way Suite 15
USA - NJ 08884 Spotswood
Tel.: +1 7324169590
e.mail: fleet089@hotmail.com

- **Emergency telephone number:**

International: 011 49(0)700 24112112 (MIP)

US: +1 872 5888271 (MIP)

US Emergency Telephone Number (for transportation incidents only): 1-800-535-5053 (Infotrac)

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS08 Health hazard

Specific Target Organ Toxicity - Repeated Exposure 2

H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word Warning**

- **Hazard-determining components of labeling:**

n-Butyl acetate

Xylene

2-Methoxy-1-methylethyl acetate

Ethylbenzene

- **Hazard statements**

H226 Flammable liquid and vapor.

Trade name: Mipa BC-Xirallic-Mischlack

(Contd. of page 1)

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a poison center/doctor if you feel unwell.

Classification system:

NFPA ratings (scale 0 - 4)



Health = 0

Fire = 3

Reactivity = 0

HMIS-ratings (scale 0 - 4)



Health = 0

Fire = 3

Reactivity = 0

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

123-86-4	n-Butyl acetate	50-100%
1330-20-7	Xylene	2.5-<5%
108-65-6	2-Methoxy-1-methylethyl acetate	2.5-<10%
78-93-3	Methyl ethyl ketone	<2.5%
100-41-4	Ethylbenzene	<2.5%

4 First-aid measures

Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately rinse with water.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: If symptoms persist consult doctor.

Information for doctor:

Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)

Trade name: Mipa BC-Xirallic-Mischlack

· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

(Contd. of page 2)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

123-86-4	n-Butyl acetate	5 ppm
1344-28-1	aluminium oxide	15 mg/m ³
1330-20-7	Xylene	130 ppm
24937-78-8	Ethyl vinyl acetate copolymer	30 mg/m ³
108-65-6	2-Methoxy-1-methylethyl acetate	50 ppm
78-93-3	Methyl ethyl ketone	200 ppm
100-41-4	Ethylbenzene	33 ppm
1309-37-1	Diiron trioxide	15 mg/m ³
67-68-5	dimethyl sulfoxide	150 ppm
85-44-9	Phthalic anhydride	18 mg/m ³
18282-10-5	tin dioxide	7.6 mg/m ³
108-88-3	Toluene	67 ppm
7447-41-8	lithium chloride	2.3 mg/m ³

· **PAC-2:**

123-86-4	n-Butyl acetate	200 ppm
1344-28-1	aluminium oxide	170 mg/m ³
1330-20-7	Xylene	920* ppm
24937-78-8	Ethyl vinyl acetate copolymer	330 mg/m ³
108-65-6	2-Methoxy-1-methylethyl acetate	1,000 ppm

(Contd. on page 4)

Trade name: Mipa BC-Xirallic-Mischlack

(Contd. of page 3)

78-93-3	Methyl ethyl ketone	2700* ppm
100-41-4	Ethylbenzene	1100* ppm
1309-37-1	Diiron trioxide	360 mg/m ³
67-68-5	dimethyl sulfoxide	290 ppm
85-44-9	Phthalic anhydride	56 mg/m ³
18282-10-5	tin dioxide	85 mg/m ³
108-88-3	Toluene	560 ppm
7447-41-8	lithium chloride	25 mg/m ³

· PAC-3:

123-86-4	n-Butyl acetate	3000* ppm
1344-28-1	aluminium oxide	990 mg/m ³
1330-20-7	Xylene	2500* ppm
24937-78-8	Ethyl vinyl acetate copolymer	2,000 mg/m ³
108-65-6	2-Methoxy-1-methylethyl acetate	5000* ppm
78-93-3	Methyl ethyl ketone	4000* ppm
100-41-4	Ethylbenzene	1800* ppm
1309-37-1	Diiron trioxide	2,200 mg/m ³
67-68-5	dimethyl sulfoxide	1,800 ppm
85-44-9	Phthalic anhydride	10,000 mg/m ³
18282-10-5	tin dioxide	510 mg/m ³
108-88-3	Toluene	3700* ppm
7447-41-8	lithium chloride	150 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.

(Contd. on page 5)

Trade name: Mipa BC-Xirallic-Mischlack

(Contd. of page 4)

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

123-86-4 n-Butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

1330-20-7 Xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm BEI, A4

108-65-6 2-Methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

78-93-3 Methyl ethyl ketone

PEL	Long-term value: 590 mg/m ³ , 200 ppm
REL	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm
TLV	Short-term value: 300 ppm Long-term value: 200 ppm BEI

100-41-4 Ethylbenzene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm OTO, BEI, A3

· **Ingredients with biological limit values:**

1330-20-7 Xylene

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

78-93-3 Methyl ethyl ketone

BEI	2 mg/L Medium: urine Time: end of shift Parameter: Methyl ethyl ketone (nonspecific)
-----	---

100-41-4 Ethylbenzene

BEI	0.15 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)
-----	---

· **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 6)

Trade name: Mipa BC-Xirallic-Mischlack

(Contd. of page 5)

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
- **Breathing equipment:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Breakthrough time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**
 - **Form:** Fluid
 - **Color:** According to product specification
 - **Odor:** Characteristic
 - **Odor threshold:** Not determined.
- **pH-value:** Not determined.
- **Change in condition**
 - **Melting point/Melting range:** Undetermined.
 - **Boiling point/Boiling range:** 124-128 °C (255.2-262.4 °F)
- **Flash point:** 23 °C (73.4 °F) (DIN EN ISO 1523:2002)
- **Flammability (solid, gaseous):** Flammable.

(Contd. on page 7)

Trade name: Mipa BC-Xirallic-Mischlack

(Contd. of page 6)

· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
· Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
· Density at 20 °C (68 °F):	0.969 g/cm ³ (8.086 lbs/gal) (DIN EN ISO 2811-1)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C (68 °F):	135 s (DIN 53211/4)
· Solvent content:	
VOC content:	72.31 % 701 g/l / 5.8 lb/gal
Solids content (weight-%):	27.8 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

123-86-4 n-Butyl acetate

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.

(Contd. on page 8)

Trade name: Mipa BC-Xirallic-Mischlack

(Contd. of page 7)

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

1330-20-7	Xylene	3
100-41-4	Ethylbenzene	2B
1309-37-1	Diiron trioxide	3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:**

Packagings that cannot be cleansed are to be disposed of in the same manner as the product.

14 Transport information

· **UN-Number**

· **DOT, ADR, IMDG, IATA** UN1263

· **UN proper shipping name**

· **DOT** Paint

· **ADR** UN1263 PAINT

· **IMDG, IATA** PAINT

(Contd. on page 9)

Trade name: Mipa BC-Xirallic-Mischlack

(Contd. of page 8)

· **Transport hazard class(es)**

· **DOT**



· **Class** 3 Flammable liquids
· **Label** 3

· **ADR**



· **Class** 3 (F1) Flammable liquids
· **Label** 3

· **IMDG, IATA**



· **Class** 3 Flammable liquids
· **Label** 3

· **Packing group**

· **DOT, ADR, IMDG, IATA** III

· **Environmental hazards:** Not applicable.

· **Special precautions for user** Warning: Flammable liquids

· **Hazard identification number (Kemler code):** 30

· **EMS Number:** F-E, S-E

· **Stowage Category** A

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)** 5L
· **Remarks:** ≤ 450 l: 2.2.3.1.5 ADR

· **IMDG**

· **Limited quantities (LQ)** 5L
· **Remarks:** ≤ 450 l: 2.3.2.5 IMDG

· **UN "Model Regulation":** UN 1263 PAINT, 3, III

USA

(Contd. on page 10)

Trade name: Mipa BC-Xirallic-Mischlack

(Contd. of page 9)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

1344-28-1	aluminium oxide
-----------	-----------------

1330-20-7	Xylene
-----------	--------

100-41-4	Ethylbenzene
----------	--------------

85-44-9	Phthalic anhydride
---------	--------------------

108-88-3	Toluene
----------	---------

· Hazardous Air Pollutants

1330-20-7	Xylene
-----------	--------

100-41-4	Ethylbenzene
----------	--------------

85-44-9	Phthalic anhydride
---------	--------------------

108-88-3	Toluene
----------	---------

· Proposition 65

· Chemicals known to cause cancer:

100-41-4	Ethylbenzene
----------	--------------

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

108-88-3	Toluene
----------	---------

· Cancerogenity categories

· EPA (Environmental Protection Agency)

1330-20-7	Xylene	I
-----------	--------	---

78-93-3	Methyl ethyl ketone	I
---------	---------------------	---

100-41-4	Ethylbenzene	D
----------	--------------	---

108-88-3	Toluene	II
----------	---------	----

· TLV (Threshold Limit Value)

1344-28-1	aluminium oxide	A4	2.5-<10%
-----------	-----------------	----	----------

1330-20-7	Xylene	A4	2.5-<5%
-----------	--------	----	---------

100-41-4	Ethylbenzene	A3	<2.5%
----------	--------------	----	-------

1309-37-1	Diiron trioxide	A4	<1%
-----------	-----------------	----	-----

85-44-9	Phthalic anhydride	A4	<0.1%
---------	--------------------	----	-------

108-88-3	Toluene	A4	<0.1%
----------	---------	----	-------

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 11)

Trade name: Mipa BC-Xirallic-Mischlack

(Contd. of page 10)

Hazard pictograms



GHS02 GHS07 GHS08

Signal word Warning

Hazard-determining components of labeling:

n-Butyl acetate
Xylene
2-Methoxy-1-methylethyl acetate
Ethylbenzene

Hazard statements

H226 Flammable liquid and vapor.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a poison center/doctor if you feel unwell.

National regulations:

Additional classification according to Decree on Hazardous Materials:

Class	Share in %
NK	50-100

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Contact:

Date of preparation / last revision 05/09/2023

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit

(Contd. on page 12)

Safety Data Sheet
acc. to OSHA HCS

Printing date 05/09/2023

Reviewed on 05/09/2023

Trade name: Mipa BC-Xirallic-Mischlack

(Contd. of page 11)

BEI: Biological Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2

· * **Data compared to the previous version altered.**

USA