Reviewed on 10/02/2024

Fleetwood Products Inc.



Printing date 10/02/2024

1 Identification

- · Product identifier
- Trade name: Mipa Bumper Paint
- · Application of the substance / the mixture Paint
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: MIPA SE Am Oberen Moos 1 D-84051 Essenbach Tel.: +49(0)8703-922-0 Fax.: +49(0)8703-922-100 e-mail: sdb-registratur@mipa-paints.com www.mipa-paints.com Emergency telephone number:

13 American Way Suite 15 USA - NJ 08884 Spotswood Tel.: +1 7324169590 e.mail: fleet089@hotmail.com

US: +1 872 5888271 (MIP) US Emergency Telephone Number (for transportation incidents only): 1-800-535-5053 (Infotrac)

Safety Data Sheet

acc. to OSHA HCS

2 Hazard(s) identification

· Classification of the substance or mixture

International: 011 49(0)700 24112112 (MIP)



Flammable Liquids 3

H226 Flammable liquid and vapor.



Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

· Label elements

· GHS label elements

- The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Warning

- · Hazard-determining components of labeling: n-Butyl acetate
- 2-Methoxy-1-methylethyl acetate
- Hydrocarbons, C9, aromatics
- · Hazard statements
- H226 Flammable liquid and vapor.

H336 May cause drowsiness or dizziness.

- · Precautionary statements
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P261
 - Avoid breathing dust/fume/gas/mist/vapors/spray
- Wear protective gloves/protective clothing/eye protection/face protection. P280
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

(Contd. on page 2)

- USA



Safety Data Sheet

acc. to OSHA HCS

Reviewed on 10/02/2024

Trade name: Mipa Bumper Paint

P304+P340 P312 • Classification s	(Contd. of page 1) IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. system:
· NFPA ratings (s	
Mi i A latings (scare o - 4/
Fire	alth = 0 e = 3 activity = 0
· HMIS-ratings (s	cale 0 - 4)
FIRE 3 Fi	ealth = 0 re = 3 eactivity = 0
· Other hazards	
	and vPvB assessment
• PBT: Not application	able.
• vPvB: Not applie	cable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
123-86-4	n-Butyl acetate	25-50%
108-65-6	2-Methoxy-1-methylethyl acetate	2.5-<10%
64742-95-6	Hydrocarbons, C9, aromatics	1-<2.5%
112-07-2	2-Butoxyethyl acetate	1-<2.5%

4 First-aid measures

· Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

(Contd. of page 2)

Safety Data Sheet

acc. to OSHA HCS

Reviewed on 10/02/2024



Printing date 10/02/2024

Trade name: Mipa Bumper Paint

· Advice for firefighters

· Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13.
- Ensure adequate ventilation. • **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.
- Protective Action Criteria for Chemicals

· PAC-1:		
123-86-4	n-Butyl acetate	5 ppm
108-65-6	2-Methoxy-1-methylethyl acetate	50 ppm
112-07-2	2-Butoxyethyl acetate	15 ppm
· PAC-2:		
123-86-4	n-Butyl acetate	200 ppm
108-65-6	2-Methoxy-1-methylethyl acetate	1,000 ppm
112-07-2	2-Butoxyethyl acetate	35 ppm
· PAC-3:		
123-86-4	n-Butyl acetate	3000* ppm
108-65-6	2-Methoxy-1-methylethyl acetate	5000* ppm
112-07-2	2-Butoxyethyl acetate	210 ppm

7 Handling and storage

· Handling:

- **Precautions for safe handling** Use only in well ventilated areas. Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

(Contd. on page 4)

USA



Safety Data Sheet

acc. to OSHA HCS

Reviewed on 10/02/2024

Trade name: Mipa Bumper Paint

(Contd. of page 3)

8 Exposure controls/personal protection · Additional information about design of technical systems: No further data; see section 7. · Control parameters · Components with limit values that require monitoring at the workplace: The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the remaining constituent has no known exposure limits. 123-86-4 n-Butyl acetate PEL Long-term value: 710 mg/m³, 150 ppm Short-term value: 950 mg/m³, 200 ppm REL Long-term value: 710 mg/m³, 150 ppm TLV Short-term value: 150 ppm Long-term value: 50 ppm 108-65-6 2-Methoxy-1-methylethyl acetate WEEL Long-term value: 50 ppm 112-07-2 2-Butoxyethyl acetate REL Long-term value: 33 mg/m³, 5 ppm TLV Long-term value: 20 ppm A3 · Additional information: The lists that were valid during the creation were used as basis. · Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.
- · Breathing equipment:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

USA

(Contd. of page 4)



Printing date 10/02/2024

Safety Data Sheet acc. to OSHA HCS

Reviewed on 10/02/2024

Trade name: Mipa Bumper Paint

· Eye protection:



Tightly sealed goggles

Information on basic physical and c	chemical properties
General Information	
Appearance:	
Form:	Fluid
Color: Odor:	According to product specification Characteristic
Odor: Odor threshold:	Not determined.
pH-value:	Not determined.
•	
Change in condition Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	124-128 °C (255.2-262.4 °F)
Flash point:	27 °C (80.6 °F) (DIN 53213)
Flammability:	Flammable.
Auto igniting:	315 °C (599 °F) (DIN 51794)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosiv air/vapor mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
Vapor pressure at 50 °C (122 °F):	55 hPa (41.3 mm Hg)
Density at 20 °C (68 °F):	0.968 g/cm³ (8.078 lbs/gal) (DIN 53217)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C (68 °F):	>60 s (ISO 6 mm)
Solvent content:	
VOC content:	49.22 %
	476 g/l / 4.0 lb/gal
Solids content (weight-%):	50.6 %



Safety Data Sheet

acc. to OSHA HCS

Reviewed on 10/02/2024

Trade name: Mipa Bumper Paint

(Contd. of page 5)

· Other information

No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
 Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

Carcinogenic categories

5	5	
· IARC (Inter	national Agency for Research on Cancer)	
13463-67-7	Titanium dioxide	2B
7631-86-9	Silicon dioxide, chemically prepared	3
1333-86-4	Carbon black	2B
1330-20-7	Xylene	3
14807-96-6	Talc	3
9002-88-4	Polyethylene low density	3
100-41-4	Ethylbenzene	2B
· NTP (Natio	nal Toxicology Program)	
50-00-0 fori	50-00-0 formaldehyde K	
· OSHA-Ca (Occupational Safety & Health Administration)	
50-00-0 fori	maldehyde	

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 7)

USA



Trade name: Mipa Bumper Paint

Reviewed on 10/02/2024

(Contd. of page 6)

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

• Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Safety Data Sheet

acc. to OSHA HCS

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

UN-Number DOT, ADR, IMDG, IATA	UN1263	
UN proper shipping name	011203	
DOT	Paint	
ADR	UN1263 PAINT	
IMDG, IATA	PAINT	
Transport hazard class(es)		
DOT		
FLAMABLE LIOUD		
V		
Class	3 Flammable liquids	
Label	3	
ADR		
3		
Class	3 (F1) Flammable liquids	
Label	3	
IMDG, IATA		
►, ▲		
V		
Class	3 Flammable liquids	
Label	3	
Packing group		
DOT, ADR, IMDG, IATA	III	
Environmental hazards:		
Marine pollutant:	No	



Safety Data Sheet

acc. to OSHA HCS

Reviewed on 10/02/2024

Trade name: Mipa Bumper Paint

	(Contd. of page
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler cod	e): 30
EMS Number:	F-E, <u>S-E</u>
Stowage Category	A
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Remarks:	≤ 450 l: 2.2.3.1.5 ADR
IMDG	
Limited quantities (LQ)	5L
Remarks:	≤ 450 l: 2.3.2.5 IMDG-Code
UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

[·] Sara

 Section 355 (extremely hazardous substances): 	
50-00-0 formaldehyde	

- · Section 313 (Specific toxic chemical listings):
- 112-07-2 2-Butoxyethyl acetate

· Proposition 65

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

• Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

TLV (Threshold Limit Value)

112-07-2 2-Butoxyethyl acetate

A3 1-<2.5%

· NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7 Titanium dioxide

- 1333-86-4 Carbon black
- 50-00-0 formaldehyde

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



(Contd. on page 9)

USA



Trade name: Mipa Bumper Paint

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health

** Data compared to the previous version altered.

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Reviewed on 10/02/2024

Trade name: Mipa Bumper Paint
(Contd. of page 8)
· Signal word Warning
· Hazard-determining components of labeling:
n-Butyl acetate
2-Methoxy-1-methylethyl acetate
Hydrocarbons, C9, aromatics
Hazard statements
H226 Flammable liquid and vapor.
H336 May cause drowsiness or dizziness.
· Precautionary statements
P210 Keep away from heat/sparks/open flames/hot surfaces No smoking. P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P261Avoid breathing dust/fume/gas/mist/vapors/sprayP280Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin
with water/shower.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a poison center/doctor if you feel unwell.
· National regulations:
Additional classification according to Decree on Hazardous Materials:
Class Share in %
NK 25-50
· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.
16 Other information
This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
· Contact:
Date of preparation / last revision 10/02/2024 / 44
· Abbreviations and acronyms:
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations
Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning
the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: verv Persistent and verv Bioaccumulative

Flammable Liquids 3: Flammable liquids – Category 3 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

Safety Data Sheet acc. to OSHA HCS

USA