Fleetwood Products Inc.

Tel.: +1 7324169590

13 American Way Suite 15 USA - NJ 08884 Spotswood

e.mail: fleet089@hotmail.com



Safety Data Sheet

acc. to OSHA HCS

Printing date 08/22/2024 Reviewed on 08/22/2024

1 Identification

- · Product identifier
- · Trade name: Mipa EP-Multi-Filler HB 2.1
- · Application of the substance / the mixture Paint
- · Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49(0)8703-922-0

Fax.: +49(0)8703-922-100 e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

· Emergency telephone number:

International: 011 49(0)700 24112112 (MIP)

US: +1 872 5888271 (MIP)

US Emergency Telephone Number (for transportation incidents only): 1-800-535-5053 (Infotrac)

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2 H225 Highly flammable liquid and vapor.



Skin Irritation 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms





GHS02 GHS07

1002 G0301

· Signal word Danger

· Hazard-determining components of labeling:

Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight =< 700)

4-chloro-alpha,alpha,alpha-trifluorotoluene

· Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

(Contd. on page 2)



acc. to OSHA HCS

Reviewed on 08/22/2024 Printing date 08/22/2024

Trade name: Mipa EP-Multi-Filler HB 2.1

(Contd. of page 1)

Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P363 Wash contaminated clothing before reuse.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2Fire = 3

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable. vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
	Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight =< 700)	25-50%
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	10-25%
78-93-3	Methyl ethyl ketone	2.5-<10%
64742-95-6	Hydrocarbons, C9, aromatics	2.5-<5%

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.



acc. to OSHA HCS

Printing date 08/22/2024 Reviewed on 08/22/2024

Trade name: Mipa EP-Multi-Filler HB 2.1

(Contd. of page 2)

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

· PAC-1:		
25068-38-6	Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (numb average molecular weight =< 700)	er 90 mg/m³
78-93-3	Methyl ethyl ketone	200 ppm
PAC-2:		
25068-38-6	Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (numbe average molecular weight =< 700)	r 990 mg/m³
78-93-3	Methyl ethyl ketone	2700* ppm
PAC-3:		
25068-38-6	Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight =< 700)	5,900 mg/m³
	arerage merecanar resigns	

7 Handling and storage

- Handling:
- · Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- Storage
- Requirements to be met by storerooms and receptacles: Store in a cool location.

(Contd. on page 4)



acc. to OSHA HCS

Printing date 08/22/2024 Reviewed on 08/22/2024

Trade name: Mipa EP-Multi-Filler HB 2.1

(Contd. of page 3)

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

78-93-3 Methyl ethyl ketone

PEL Long-term value: 590 mg/m³, 200 ppm

REL | Short-term value: 885 mg/m³, 300 ppm

Long-term value: 590 mg/m³, 200 ppm

TLV Short-term value: 150 ppm

Long-term value: 75 ppm

BEI, Skin

Ingredients with biological limit values:

78-93-3 Methyl ethyl ketone

BEI 2 mg/L

Medium: urine Time: end of shift

Parameter: Methyl ethyl ketone (nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Breathing equipment:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)



acc. to OSHA HCS

Printing date 08/22/2024 Reviewed on 08/22/2024

Trade name: Mipa EP-Multi-Filler HB 2.1

(Contd. of page 4)

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and o · General Information	chemical properties
· Appearance: Form: Color: · Odor: · Odor threshold:	Fluid According to product specification Characteristic Not determined.
· pH-value:	Not determined.
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 139 °C (282.2 °F)
· Flash point:	20 °C (68 °F) (DIN EN ISO 1523:2002)
· Flammability (solid, gaseous):	Highly flammable.
· Auto igniting:	460 °C (860 °F) (DIN 51794)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits: Lower: Upper:	0.7 Vol % 7.5 Vol %
· Vapor pressure at 20 °C (68 °F): · Vapor pressure at 50 °C (122 °F):	<0.1 hPa 38.6 hPa (29 mm Hg)
Density at 20 °C (68 °F):	1.612 g/cm³ (13.452 lbs/gal) (DIN EN ISO 2811-1)

Relative density

Not determined.

Relative density
 Vapor density
 Evaporation rate
 Not determined.
 Not determined.

Water: Not miscible or difficult to mix.

· Solubility in / Miscibility with

· Partition coefficient (n-octanol/water): Not determined.

(Contd. on page 6)



acc. to OSHA HCS

Printing date 08/22/2024 Reviewed on 08/22/2024

Trade name: Mipa EP-Multi-Filler HB 2.1

	(Contd. of page
· Viscosity: Dynamic at 20 °C (68 °F): Kinematic:	10,000 mPas Not determined.
· Solvent content: VOC content:	9.27 % 171 g/l / 1.4 lb/gal
Solids content (weight-%):	80.3 %
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

. Irritant

· Carcinogenic categories

· IARC (Intern	· IARC (International Agency for Research on Cancer)		
14807-96-6	Talc	3	
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	2B	
13463-67-7	Titanium dioxide	2B	
· NTP (Nation	· NTP (National Toxicology Program)		
None of the	None of the ingredients is listed.		
· OSHA-Ca (Occupational Safety & Health Administration)			
None of the ingredients is listed.			

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.

(Contd. on page 7)



acc. to OSHA HCS

Printing date 08/22/2024 Reviewed on 08/22/2024

Trade name: Mipa EP-Multi-Filler HB 2.1

(Contd. of page 6)

- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

	_		 rmat	
71	rone	POP	rmat	ION
			 1 	

· UN-Number · DOT, ADR, IMDG, IATA	UN1263
· UN proper shipping name	
·DOT	Paint
· ADR	UN1263 PAINT, ENVIRONMENTALLY HAZARDOUS
· IMDG	PAINT (Bisphenolresins, CHLOROBENZOTRIFLUORIDES), MARINE POLLUTANT
· IATA	PAINT

- · Transport hazard class(es)
- DOT



· Class 3 Flammable liquids · Label 3

· ADR



· Class 3 (F1) Flammable liquids

(Contd. on page 8)



acc. to OSHA HCS

Printing date 08/22/2024 Reviewed on 08/22/2024

Trade name: Mipa EP-Multi-Filler HB 2.1

(Contd. of page 7) ·Label · IMDG 3 Flammable liquids · Class · Label ·IATA 3 Flammable liquids · Class · Label 3 · Packing group · DOT, ADR, IMDG, IATA 11 · Environmental hazards: Product contains environmentally hazardous substances: Trizinc bis(orthophosphate), Bisphenolresins · Marine pollutant: Yes Symbol (fish and tree) · Special marking (ADR): Symbol (fish and tree) · Special precautions for user Warning: Flammable liquids Hazard identification number (Kemler code): 33 · EMS Number: F-E,S-E · Stowage Category R · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: · Remarks: Special marking with the symbol (fish and tree). · ADR · Limited quantities (LQ) 5L Limited quantities (LQ) 5L · UN "Model Regulation": UN 1263 PAINT, 3, II, ENVIRONMENTALLY **HAZARDOUS**

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

(Contd. on page 9)



acc. to OSHA HCS

Printing date 08/22/2024 Reviewed on 08/22/2024

Trade name: Mipa EP-Multi-Filler HB 2.1

(Contd. of page 8)

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

Cancerogenity categories

· EPA (Environmental Protection Agency)

78-93-3 Methyl ethyl ketone

| | |

· NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7 Titanium dioxide

1333-86-4 Carbon black

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms





GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labeling:

Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight =< 700)

4-chloro-alpha,alpha,alpha-trifluorotoluene

Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P363 Wash contaminated clothing before reuse.

· National regulations:

Additional classification according to Decree on Hazardous Materials:

Class	Share in %
NK	10-25

(Contd. on page 10)



acc. to OSHA HCS

Printing date 08/22/2024 Reviewed on 08/22/2024

Trade name: Mipa EP-Multi-Filler HB 2.1

(Contd. of page 9)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Contact:
- · Date of preparation / last revision 08/22/2024 / -
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, ÉU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Skin Irritation 2: Skin corrosion/irritation - Category 2

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Sensitization - Skin 1: Skin sensitisation - Category 1

* * Data compared to the previous version altered.

USA