

1 Identification

- **Product identifier**
 - **Trade name: Mipa N 30 NC-Auto-Spachtel**
 - **Application of the substance / the mixture** Knife filler/ Surfacer
 - **Details of the supplier of the safety data sheet**
 - **Manufacturer/Supplier:**
MIPA SE
Am Oberen Moos 1
D-84051 Essenbach
Tel.: +49(0)8703-922-0
Fax.: +49(0)8703-922-100
e-mail: sdb-registratur@mipa-paints.com
www.mipa-paints.com
 - **Emergency telephone number:**
International: 011 49(0)700 24112112 (MIP)
US: +1 872 5888271 (MIP)
US Emergency Telephone Number (for transportation incidents only): 1-800-535-5053 (Infotrac)
- Fleetwood Products Inc.
13 American Way Suite 15
USA - NJ 08884 Spotswood
Tel.: +1 7324169590
e.mail: fleet089@hotmail.com

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS07

Eye Irritation 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning

- **Hazard-determining components of labeling:**

n-Butyl acetate
2-Methoxy-1-methylethyl acetate
Butan-1-ol

- **Hazard statements**

H226 Flammable liquid and vapor.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

- **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray

Trade name: Mipa N 30 NC-Auto-Spachtel

(Contd. of page 1)

- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 3
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



HEALTH *2 Health = *2
FIRE 3 Fire = 3
REACTIVITY 0 Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

123-86-4	n-Butyl acetate	10-25%
9004-70-0	Nitrocellulose, nitrogen content <12,6%	2.5-<10%
108-65-6	2-Methoxy-1-methylethyl acetate	2.5-<10%
71-36-3	Butan-1-ol	≥1-<2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

USA

(Contd. on page 3)

Trade name: Mipa N 30 NC-Auto-Spachtel

(Contd. of page 2)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

123-86-4	n-Butyl acetate	5 ppm
108-65-6	2-Methoxy-1-methylethyl acetate	50 ppm
13463-67-7	Titanium dioxide	30 mg/m ³
71-36-3	Butan-1-ol	60 ppm
112945-52-5	Silicon dioxide	18 mg/m ³
112-07-2	2-Butoxyethyl acetate	15 ppm
67-63-0	propan-2-ol	400 ppm
1330-20-7	Xylene	130 ppm
1317-61-9	Triiron tetraoxide	21 mg/m ³
100-41-4	Ethylbenzene	33 ppm
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³
1309-37-1	Diiron trioxide	15 mg/m ³

· PAC-2:

123-86-4	n-Butyl acetate	200 ppm
108-65-6	2-Methoxy-1-methylethyl acetate	1,000 ppm
13463-67-7	Titanium dioxide	330 mg/m ³
71-36-3	Butan-1-ol	800 ppm
112945-52-5	Silicon dioxide	100 mg/m ³
112-07-2	2-Butoxyethyl acetate	35 ppm
67-63-0	propan-2-ol	2000* ppm
1330-20-7	Xylene	920* ppm
1317-61-9	Triiron tetraoxide	230 mg/m ³
100-41-4	Ethylbenzene	1100* ppm

(Contd. on page 4)

Trade name: Mipa N 30 NC-Auto-Spachtel

(Contd. of page 3)

14808-60-7	Quartz (SiO ₂)	33 mg/m ³
1309-37-1	Diiron trioxide	360 mg/m ³
· PAC-3:		
123-86-4	n-Butyl acetate	3000* ppm
108-65-6	2-Methoxy-1-methylethyl acetate	5000* ppm
13463-67-7	Titanium dioxide	2,000 mg/m ³
71-36-3	Butan-1-ol	8000** ppm
112945-52-5	Silicon dioxide	630 mg/m ³
112-07-2	2-Butoxyethyl acetate	210 ppm
67-63-0	propan-2-ol	12000** ppm
1330-20-7	Xylene	2500* ppm
1317-61-9	Triiron tetraoxide	1,400 mg/m ³
100-41-4	Ethylbenzene	1800* ppm
14808-60-7	Quartz (SiO ₂)	200 mg/m ³
1309-37-1	Diiron trioxide	2,200 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Use only in well ventilated areas.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

123-86-4 n-Butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

(Contd. on page 5)

Trade name: Mipa N 30 NC-Auto-Spachtel

(Contd. of page 4)

108-65-6 2-Methoxy-1-methylethyl acetate

WEEL Long-term value: 50 ppm

71-36-3 Butan-1-ol

PEL Long-term value: 300 mg/m³, 100 ppm

REL Ceiling limit value: 150 mg/m³, 50 ppm
Skin

TLV Long-term value: 20 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Breakthrough time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

Trade name: Mipa N 30 NC-Auto-Spachtel

(Contd. of page 5)

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid
Color: According to product specification

· Odor: Characteristic

· Odor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 124-128 °C (255.2-262.4 °F)

· Flash point: 30 °C (86 °F) (DIN 53213)

· Flammability (solid, gaseous): Flammable.

· Ignition temperature: 160 °C (320 °F) (DIN 51794)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower: 1.2 Vol %
Upper: 7.5 Vol %

· Vapor pressure at 20 °C (68 °F): 10.7 hPa (8 mm Hg)

· Density at 20 °C (68 °F): 1.471 g/cm³ (12.275 lbs/gal) (DIN 53217)

· Relative density: Not determined.

· Vapor density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic at 20 °C (68 °F): 30,200-77,500 mPas
Kinematic: Not determined.

· Solvent content:

VOC content: 31.16 %
458 g/l / 3.8 lb/gal

Solids content (weight-%): 68.8 %

· Other information: No further relevant information available.

10 Stability and reactivity

· Reactivity: No further relevant information available.

· Chemical stability

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· Possibility of hazardous reactions: No dangerous reactions known.

(Contd. on page 7)

Trade name: Mipa N 30 NC-Auto-Spachtel

(Contd. of page 6)

- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
 - **on the skin:** No irritant effect.
 - **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

14807-96-6	Talc	3
13463-67-7	Titanium dioxide	2B
67-63-0	propan-2-ol	3
1330-20-7	Xylene	3

- **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO ₂)	K
------------	----------------------------	---

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

USA

(Contd. on page 8)




Trade name: Mipa N 30 NC-Auto-Spachtel

(Contd. of page 7)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	
· DOT, ADR, IMDG, IATA	UN1263
· UN proper shipping name	
· DOT	Paint
· ADR	UN1263 PAINT
· IMDG, IATA	PAINT
· Transport hazard class(es)	
· DOT	
	
· Class	3 Flammable liquids
· Label	3
· ADR	
	
· Class	3 (F1) Flammable liquids
· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E, S-E
· Stowage Category	A

(Contd. on page 9)

Trade name: Mipa N 30 NC-Auto-Spachtel

(Contd. of page 8)

- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
- **Transport/Additional information:**
- **ADR**
- **Limited quantities (LQ)** 5L
- **Remarks:** ≤ 450 l: 2.2.3.1.5 ADR
- **IMDG**
- **Limited quantities (LQ)** 5L
- **Remarks:** ≤ 450 l: 2.3.2.5 IMDG
- **UN "Model Regulation":** UN 1263 PAINT, 3, III

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

71-36-3	Butan-1-ol
7429-90-5	aluminium powder (stabilized)/ manufacturer classification
112-07-2	2-Butoxyethyl acetate
67-63-0	propan-2-ol
1330-20-7	Xylene
100-41-4	Ethylbenzene

· **Hazardous Air Pollutants**

1330-20-7	Xylene
100-41-4	Ethylbenzene

· **Proposition 65**

· **Chemicals known to cause cancer:**

13463-67-7	Titanium dioxide
100-41-4	Ethylbenzene
14808-60-7	Quartz (SiO ₂)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogeny categories**

· **EPA (Environmental Protection Agency)**

71-36-3	Butan-1-ol	D
1330-20-7	Xylene	I
100-41-4	Ethylbenzene	D

(Contd. on page 10)

Trade name: Mipa N 30 NC-Auto-Spachtel

(Contd. of page 9)

· TLV (Threshold Limit Value)

14807-96-6	Talc	A4	10-25%
13463-67-7	Titanium dioxide	A4	2.5-<10%
7429-90-5	aluminium powder (stabilized)/ manufacturer classification	A4	<1%
112-07-2	2-Butoxyethyl acetate	A3	<1%
67-63-0	propan-2-ol	A4	<1%
1330-20-7	Xylene	A4	<1%
100-41-4	Ethylbenzene	A3	<0.1%
14808-60-7	Quartz (SiO ₂)	A2	<0.1%
1309-37-1	Diiron trioxide	A4	<0.1%

· NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7	Titanium dioxide
14808-60-7	Quartz (SiO ₂)

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms


GHS02 GHS07

· Signal word Warning
· Hazard-determining components of labeling:

n-Butyl acetate
 2-Methoxy-1-methylethyl acetate
 Butan-1-ol

· Hazard statements

H226 Flammable liquid and vapor.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P261 Avoid breathing dust/fume/gas/mist/vapors/spray
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

· National regulations:
· Additional classification according to Decree on Hazardous Materials:

Class	Share in %
NK	25-50

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 11)

Trade name: Mipa N 30 NC-Auto-Spachtel

(Contd. of page 10)

· **Contact:**

· **Date of preparation / last revision 02/28/2023**

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

· *** Data compared to the previous version altered.**