Reviewed on 02/28/2023



Printing date 02/28/2023

1 Identification

- · Product identifier
- Trade name: Mipa P 50 PE-Faserspachtel
- · Application of the substance / the mixture Knife filler/ Surfacer
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: MIPA SE Am Oberen Moos 1 D-84051 Essenbach Tel.: +49(0)8703-922-0 Fax.: +49(0)8703-922-100 e-mail: sdb-registratur@mipa-paints.com www.mipa-paints.com Emergency telephone number:

Fleetwood Products Inc. 13 American Way Suite 15 USA - NJ 08884 Spotswood Tel.: +1 7324169590 e.mail: fleet089@hotmail.com

US: +1 872 5888271 (MIP) US Emergency Telephone Number (for transportation incidents only): 1-800-535-5053 (Infotrac)

Safety Data Sheet

acc. to OSHA HCS

2 Hazard(s) identification

· Classification of the substance or mixture

International: 011 49(0)700 24112112 (MIP)



GHS02 Flame

Flammable Liquids 3



GHS08 Health hazard

Toxic to Reproduction 2

Specific Target Organ Toxicity - Repeated Exposure 1

GHS07

H226 Flammable liquid and vapor.

H361 Suspected of damaging fertility or the unborn child.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

H315 Causes skin irritation. Skin Irritation 2 Eye Irritation 2A H319 Causes serious eye irritation. Sensitization - Skin 1 H317 May cause an allergic skin reaction.

· Label elements

- · GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling: Styrene

(Contd. on page 2)

USA



Reviewed on 02/28/2023

Trade name: Mipa P 50 PE-Faserspachtel

(Contd. of page 1) Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl] (4-methylphenyl)amino]- maleic anhydride • Hazard statements H226 Flammable liquid and vapor. H315 Causes skin irritation.
H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H361 Suspected of damaging fertility or the unborn child. H372 Causes damage to the hearing organs through prolonged or repeated exposure.
 Precautionary statements P210 Keep away from heat/sparks/open flames/hot surfaces No smoking. P260 Do not breathe dust/fume/gas/mist/vapors/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection. P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P363 Wash contaminated clothing before reuse. Classification system: NFPA ratings (scale 0 - 4)
Health = 2 Fire = 3 Reactivity = 0
HMIS-ratings (scale 0 - 4) HEALTH *2 FIRE 3 Fire = 3 Reactivity 0
• Other hazards • Results of PBT and vPvB assessment • PBT: Not applicable. • vPvB: Not applicable.
3 Composition/information on ingredients
• Chemical characterization: Mixtures • Description: Mixture of the substances listed below with nonhazardous additions.
· Dangerous components:

Safety Data Sheet acc. to OSHA HCS

-		
100-42-5	Styrene	≥10-≤20%
	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2- [[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-	≥1-<2.5%
108-31-6	maleic anhydride	<i>≥</i> 0.001-<0.1%

4 First-aid measures

· Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately rinse with water.

(Contd. on page 3) - USA

(Contd. of page 2)



Printing date 02/28/2023

Safety Data Sheet

acc. to OSHA HCS

Reviewed on 02/28/2023

Trade name: Mipa P 50 PE-Faserspachtel

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • After swallowing: If symptoms persist consult doctor.

- Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- *Indication of any immediate medical attention and special treatment needed* No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Alcohol resistant foam
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
 Wear protective equipment. Keep unprotected persons away.
 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.
- Protective Action Criteria for Chemicals

100-42-5	Styrene	20 ppm
65997-17-3	Fibrous Glass	15 mg/m³
112945-52-5	Silicon dioxide	18 mg/m³
122-99-6	2-phenoxyethanol	1.5 ppm
108-31-6	maleic anhydride	0.2 ppm
130-15-4	1,4-naphthoquinone	0.57 mg/m
67-63-0	propan-2-ol	400 ppm
PAC-2:		
100-42-5	Styrene	130 ppm
65997-17-3	Fibrous Glass	170 mg/m
112945-52-5	Silicon dioxide	100 mg/m
122-99-6	2-phenoxyethanol	16 ppm
108-31-6	maleic anhydride	2 ppm
130-15-4	1,4-naphthoquinone	6.3 mg/m ³
67-63-0	propan-2-ol	2000* ppn



Reviewed on 02/28/2023

Trade name: Mipa P 50 PE-Faserspachtel

		(Contd. of page 3)
· PAC-3:		
100-42-5	Styrene	1100* ppm
65997-17-3	Fibrous Glass	990 mg/m³
112945-52-5	Silicon dioxide	630 mg/m³
	2-phenoxyethanol	97 ppm
108-31-6	maleic anhydride	20 ppm
130-15-4	1,4-naphthoquinone	38 mg/m³
67-63-0	propan-2-ol	12000** ppm

Safety Data Sheet

acc. to OSHA HCS

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

PEL	Long-term value: 100 ppm Ceiling limit value: 200; 600* ppm	
	*5-min peak in any 3 hrs	
REL	Short-term value: 425 mg/m³, 100 ppm Long-term value: 215 mg/m³, 50 ppm	
TLV	Short-term value: 20 ppm Long-term value: 10 ppm BEI, OTO, A3	
108-3	31-6 maleic anhydride	
PEL	Long-term value: 1 mg/m³, 0.25 ppm	
REL	Long-term value: 1 mg/m³, 0.25 ppm	
		(Contd. on page

Professional Coating Systems

Printing date 02/28/2023

Safety Data Sheet

acc. to OSHA HCS

Reviewed on 02/28/2023

Trade name: Mipa P 50 PE-Faserspachtel

(Contd. of page 4) TLV Long-term value: 0.01* mg/m³ DSEN, RSEN;*inh. fraction + vapor, A4 Ingredients with biological limit values: 100-42-5 Styrene BEI 400 mg/g creatinine Medium: urine Time: end of shift Parameter: Mandelic acid plus phenylglyoxylic acid (nonspecific) 40 µg/L Medium: urine Time: end of shift Parameter: Styrene · Additional information: The lists that were valid during the creation were used as basis. Exposure controls · Personal protective equipment: · General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Breathing equipment:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

USA



Reviewed on 02/28/2023

Trade name: Mipa P 50 PE-Faserspachtel

(Contd. of page 5)

• Eye protection:



Tightly sealed goggles

Information on basic physical and	chemical properties
General Information	
Appearance: Form:	Fluid
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	145.2 °C (293.4 °F)
Flash point:	31 °C (87.8 °F) (DIN 53213)
Flammability (solid, gaseous):	Flammable.
Ignition temperature:	480 °C (896 °F) (DIN 51794)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosiv air/vapor mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	8.9 Vol %
Vapor pressure at 20 °C (68 °F):	6 hPa (4.5 mm Hg)
Density at 20 °C (68 °F):	1.595 g/cm³ (13.31 lbs/gal) (DIN 53217)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	
Viscosity:	
Dynamic at 20 °C (68 °F):	50,000-70,000 mPas
Kinematic:	Not determined.
Solvent content: VOC content:	0.27.9/
	0.27 % 4 g/l / 0.0 lb/gal
Solids content (weight-%):	79.8 %

Safety Data Sheet acc. to OSHA HCS



Safety Data Sheet

acc. to OSHA HCS

Reviewed on 02/28/2023

Trade name: Mipa P 50 PE-Faserspachtel

(Contd. of page 6)

· Other information

No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
14807-96-6 Talc	3
100-42-5 Styrene	2A
· NTP (National Toxicology Program)	
100-42-5 Styrene	R
130-15-4 1,4-naphthoquinone	R
· OSHA-Ca (Occupational Safety & Health Administration)	

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 2 (Self-assessment): hazardous for water
- Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 8)

⁻ USA

Professional Coating Systems

Printing date 02/28/2023

Safety Data Sheet

acc. to OSHA HCS

Reviewed on 02/28/2023

Trade name: Mipa P 50 PE-Faserspachtel

(Contd. of page 7)


· vPvB: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

- · Recommendation:
- Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.





Safety Data Sheet acc. to OSHA HCS

Reviewed on 02/28/2023

Trade name: Mipa P 50 PE-Faserspachtel

	(Contd. of page 8)
· EMS Number: · Stowage Category	F-E,S-D A
 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ)	5L
· IMDG · Limited quantities (LQ)	5L
· UN "Model Regulation":	UN 3269 POLYESTER RESIN KIT, 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture Sara

	355 (extremely hazardous substances):		
None of t	he ingredient is listed.		
Section 3	313 (Specific toxic chemical listings):		
100-42-5			
122-99-6	2-phenoxyethanol		
	maleic anhydride		
67-63-0	propan-2-ol		
Hazardo	is Air Pollutants		
100-42-5	Styrene		
	maleic anhydride		
130-15-4	1,4-naphthoquinone		
Proposit			
	Is known to cause cancer:		
100-42-5	Styrene		
Chemica	Is known to cause reproductive toxicity for females:		
None of t	he ingredients is listed.		
Chemica	Is known to cause reproductive toxicity for males:		
None of t	he ingredients is listed.		
Chemica	Is known to cause developmental toxicity:		
None of t	he ingredients is listed.		
Cancero	genity categories		
	vironmental Protection Agency)		
•	he ingredients is listed.		
	eshold Limit Value)		
14807-96		A4	25-50%
	-5 Styrene	A4	<i>≥10-≤</i> 20%
100-42	-6 maleic anhydride	A4	≥0.001-<0.1%

(Contd. of page 9)



Printing date 02/28/2023

Safety Data Sheet

acc. to OSHA HCS

NIOSH-Ca (National Institute for Occupational Safety and Health)

Reviewed on 02/28/2023

Trade name: Mipa P 50 PE-Faserspachtel

lone of the ingredients is listed.
GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Jazard pictograms
GHS02 GHS07 GHS08
Signal word Danger
<i>lazard-determining components of labeling:</i> Styrene Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl] 4-methylphenyl)amino]- naleic anhydride <i>lazard statements</i> 1226 Flammable liguid and vapor.
1315 Causes skin irritation. 1319 Causes serious eye irritation. 1317 May cause an allergic skin reaction. 1361 Suspected of damaging fertility or the unborn child. 1372 Causes damage to the hearing organs through prolonged or repeated exposure.
Precautionary statements
 Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Wear protective gloves/protective clothing/eye protection/face protection. Wear protective gloves/protective clothing/eye protection/face protection. Signature of the state of
P363 Wash contaminated clothing before reuse.

· National regulations:

Additional classification according to Decree on Hazardous Materials:

Class Share in %

NK 10-25

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Contact:

- · Date of preparation / last revision 02/28/2023
- · Abbreviations and acronyms: ICAO: International Civil Aviation Organisation RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 11)

USA

Professional Coating Systems

Printing date 02/28/2023

Safety Data Sheet

acc. to OSHA HCS

Reviewed on 02/28/2023

Trade name: Mipa P 50 PE-Faserspachtel

(Contd. of page 10) ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 3: Flammable liquids – Category 3 Skin Irritation 2: Skin corrosion/irritation - Category 2 Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A Sensitization - Skin 1: Skin sensitisation - Category 1 Toxic to Reproduction 2: Reproductive toxicity - Category 2 Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) - Category 1 ** Data compared to the previous version altered. USA