

1 Identification

- **Product identifier**
- **Trade name: Mipa P 97 PE-Multi-Softspachtel**
- **Application of the substance / the mixture** Knife filler/ Surfacer
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MIPA SE
Am Oberen Moos 1
D-84051 Essenbach
Tel.: +49(0)8703-922-0
Fax.: +49(0)8703-922-100
e-mail: sdb-registratur@mipa-paints.com
www.mipa-paints.com
- Fleetwood Products Inc.
13 American Way Suite 15
USA - NJ 08884 Spotswood
Tel.: +1 7324169590
e.mail: fleet089@hotmail.com
- **Emergency telephone number:**
International: 011 49(0)700 24112112 (MIP)
US: +1 872 5888271 (MIP)
US Emergency Telephone Number (for transportation incidents only): 1-800-535-5053 (Infotrac)

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS08 Health hazard

Toxic to Reproduction 2

H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure 1

H372 Causes damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irritation 2

H315 Causes skin irritation.

Eye Irritation 2A

H319 Causes serious eye irritation.

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Styrene

(Contd. on page 2)

Trade name: Mipa P 97 PE-Multi-Softspachtel

(Contd. of page 1)

maleic anhydride

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-

· **Hazard statements**

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P363 Wash contaminated clothing before reuse.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

100-42-5	Styrene	≥10-<15%
91-99-6	2,2'-(m-tolylimino)diethanol	≥0.1-<1%
	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-	≥0.1-<1%
108-31-6	maleic anhydride	≥0.001-<0.1%

4 First-aid measures

· **Description of first aid measures**

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

(Contd. on page 3)

Trade name: Mipa P 97 PE-Multi-Softspachtel

(Contd. of page 2)

- In case of unconsciousness place patient stably in side position for transportation.*
- **After skin contact:** Immediately rinse with water.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Alcohol resistant foam
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

100-42-5	Styrene	20 ppm
13463-67-7	Titanium dioxide	30 mg/m ³
64-17-5	ethanol	1,800 ppm
67-63-0	propan-2-ol	400 ppm
122-99-6	2-Phenoxyethanol	1.5 ppm
1317-61-9	Triiron tetraoxide	21 mg/m ³
71-23-8	propan-1-ol	250 ppm
78-93-3	Methyl ethyl ketone	200 ppm
108-31-6	maleic anhydride	0.2 ppm
1309-37-1	Diiron trioxide	15 mg/m ³
108-65-6	2-Methoxy-1-methylethyl acetate	50 ppm
7727-43-7	Barium sulphate, natural	15 mg/m ³
112-07-2	2-Butoxyethyl acetate	15 ppm
123-86-4	n-Butyl acetate	5 ppm

(Contd. on page 4)

Trade name: Mipa P 97 PE-Multi-Softspachtel

(Contd. of page 3)

112945-52-5	Silicon dioxide	18 mg/m ³
34590-94-8	Dipropylene glycol monomethyl ether	150 ppm
107-98-2	1-methoxy-2-propanol	100 ppm
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³

· PAC-2:

100-42-5	Styrene	130 ppm
13463-67-7	Titanium dioxide	330 mg/m ³
64-17-5	ethanol	3300* ppm
67-63-0	propan-2-ol	2000* ppm
122-99-6	2-Phenoxyethanol	16 ppm
1317-61-9	Triiron tetraoxide	230 mg/m ³
71-23-8	propan-1-ol	670 ppm
78-93-3	Methyl ethyl ketone	2700* ppm
108-31-6	maleic anhydride	2 ppm
1309-37-1	Diiron trioxide	360 mg/m ³
108-65-6	2-Methoxy-1-methylethyl acetate	1,000 ppm
7727-43-7	Barium sulphate, natural	170 mg/m ³
112-07-2	2-Butoxyethyl acetate	35 ppm
123-86-4	n-Butyl acetate	200 ppm
112945-52-5	Silicon dioxide	100 mg/m ³
34590-94-8	Dipropylene glycol monomethyl ether	1700* ppm
107-98-2	1-methoxy-2-propanol	160 ppm
14808-60-7	Quartz (SiO ₂)	33 mg/m ³

· PAC-3:

100-42-5	Styrene	1100* ppm
13463-67-7	Titanium dioxide	2,000 mg/m ³
64-17-5	ethanol	15000* ppm
67-63-0	propan-2-ol	12000** ppm
122-99-6	2-Phenoxyethanol	97 ppm
1317-61-9	Triiron tetraoxide	1,400 mg/m ³
71-23-8	propan-1-ol	4000* ppm
78-93-3	Methyl ethyl ketone	4000* ppm
108-31-6	maleic anhydride	20 ppm
1309-37-1	Diiron trioxide	2,200 mg/m ³
108-65-6	2-Methoxy-1-methylethyl acetate	5000* ppm
7727-43-7	Barium sulphate, natural	990 mg/m ³
112-07-2	2-Butoxyethyl acetate	210 ppm
123-86-4	n-Butyl acetate	3000* ppm
112945-52-5	Silicon dioxide	630 mg/m ³
34590-94-8	Dipropylene glycol monomethyl ether	9900** ppm
107-98-2	1-methoxy-2-propanol	660 ppm
14808-60-7	Quartz (SiO ₂)	200 mg/m ³

USA

(Contd. on page 5)

Trade name: Mipa P 97 PE-Multi-Softspachtel

(Contd. of page 4)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

100-42-5 Styrene

PEL	Long-term value: 100 ppm Ceiling limit value: 200; 600* ppm *5-min peak in any 3 hrs
REL	Short-term value: 425 mg/m ³ , 100 ppm Long-term value: 215 mg/m ³ , 50 ppm
TLV	Short-term value: 20 ppm Long-term value: 10 ppm BEI, OTO, A3

108-31-6 maleic anhydride

PEL	Long-term value: 1 mg/m ³ , 0.25 ppm
REL	Long-term value: 1 mg/m ³ , 0.25 ppm
TLV	Long-term value: 0.01* mg/m ³ DSEN, RSEN,*inh. fraction + vapor, A4

- **Ingredients with biological limit values:**

100-42-5 Styrene

BEI	400 mg/g creatinine Medium: urine Time: end of shift Parameter: Mandelic acid plus phenylglyoxylic acid (nonspecific)
	40 µg/L Medium: urine Time: end of shift Parameter: Styrene

(Contd. on page 6)

Trade name: Mipa P 97 PE-Multi-Softspachtel

(Contd. of page 5)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Breakthrough time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Fluid

Color:

According to product specification

· **Odor:**

Characteristic

· **Odor threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

145.2 °C (293.4 °F)

(Contd. on page 7)

Trade name: Mipa P 97 PE-Multi-Softspachtel

(Contd. of page 6)

· Flash point:	34 °C (93.2 °F) (DIN EN ISO 1523:2002)
· Flammability (solid, gaseous):	Flammable.
· Ignition temperature:	480 °C (896 °F) (DIN 51794)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	8.9 Vol %
· Vapor pressure at 20 °C (68 °F):	6 hPa (4.5 mm Hg)
· Density at 20 °C (68 °F):	1.855 g/cm ³ (15.48 lbs/gal) (DIN EN ISO 2811-1)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic at 20 °C (68 °F):	72,500-87,500 mPas
Kinematic:	Not determined.
· Solvent content:	
VOC content:	0.99 % 18 g/l / 0.2 lb/gal
Solids content (weight-%):	86.2 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.

(Contd. on page 8)

Trade name: Mipa P 97 PE-Multi-Softspachtel

(Contd. of page 7)

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

14807-96-6	Talc	3
100-42-5	Styrene	2A
13463-67-7	Titanium dioxide	2B
64-17-5	ethanol	1
67-63-0	propan-2-ol	3

· **NTP (National Toxicology Program)**

100-42-5	Styrene	R
14808-60-7	Quartz (SiO ₂)	K

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· **DOT, ADR, IMDG, IATA**

UN3269

(Contd. on page 9)

Trade name: Mipa P 97 PE-Multi-Softspachtel

(Contd. of page 8)

· **UN proper shipping name**
· **DOT** Polyester resin kit
· **ADR** UN3269 POLYESTER RESIN KIT
· **IMDG, IATA** POLYESTER RESIN KIT

· **Transport hazard class(es)**

· **DOT**



· **Class** 3 Flammable liquids
· **Label** 3

· **ADR**



· **Class** 3 (F3) Flammable liquids
· **Label** 3

· **IMDG, IATA**



· **Class** 3 Flammable liquids
· **Label** 3

· **Packing group**

· **DOT, ADR, IMDG, IATA** III

· **Environmental hazards:**

· **Marine pollutant:** No

· **Special precautions for user**

Warning: Flammable liquids

· **Hazard identification number (Kemler code):** -

· **EMS Number:**

F-E,S-D

· **Stowage Category**

A

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)** 5L

· **IMDG**

· **Limited quantities (LQ)** 5L

· **UN "Model Regulation":**

UN 3269 POLYESTER RESIN KIT, 3, III

Trade name: Mipa P 97 PE-Multi-Softspachtel

(Contd. of page 9)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

100-42-5	Styrene
67-63-0	propan-2-ol
122-99-6	2-Phenoxyethanol
108-31-6	maleic anhydride
7727-43-7	Barium sulphate, natural
112-07-2	2-Butoxyethyl acetate

· Hazardous Air Pollutants

100-42-5	Styrene
108-31-6	maleic anhydride

· Proposition 65

· Chemicals known to cause cancer:

100-42-5	Styrene
13463-67-7	Titanium dioxide
14808-60-7	Quartz (SiO ₂)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

64-17-5	ethanol
---------	---------

· Cancerogeny categories

· EPA (Environmental Protection Agency)

78-93-3	Methyl ethyl ketone	I
7727-43-7	Barium sulphate, natural	D, CBD(inh), NL(oral)

· TLV (Threshold Limit Value)

14807-96-6	Talc	A4	25-50%
100-42-5	Styrene	A4	≥10-<15%
13463-67-7	Titanium dioxide	A4	2.5-<10%
1344-95-2	Silicic acid, calcium salt	A4	<2.5%
64-17-5	ethanol	A3	<1%
67-63-0	propan-2-ol	A4	<1%
71-23-8	propan-1-ol	A4	<0.1%
108-31-6	maleic anhydride	A4	≥0.001-<0.1%
1309-37-1	Diiron trioxide	A4	<0.1%
128-37-0	Butylated hydroxytoluene	A4	<0.1%
112-07-2	2-Butoxyethyl acetate	A3	<0.1%
14808-60-7	Quartz (SiO ₂)	A2	<0.1%

(Contd. on page 11)

Trade name: Mipa P 97 PE-Multi-Softspachtel

(Contd. of page 10)

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7 Titanium dioxide

14808-60-7 Quartz (SiO₂)

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Styrene

maleic anhydride

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl] (4-methylphenyl)amino]-

· **Hazard statements**

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P363 Wash contaminated clothing before reuse.

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials:**

Class	Share in %
NK	10-25

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Contact:**

· **Date of preparation / last revision** 01/10/2023

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

(Contd. on page 12)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/10/2023

Reviewed on 01/10/2023

Trade name: Mipa P 97 PE-Multi-Softspachtel

(Contd. of page 11)

EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flammable Liquids 3: Flammable liquids – Category 3
Skin Irritation 2: Skin corrosion/irritation – Category 2
Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A
Sensitization - Skin 1: Skin sensitisation – Category 1
Toxic to Reproduction 2: Reproductive toxicity – Category 2
Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) – Category 1

*** Data compared to the previous version altered.**

USA