Fleetwood Products Inc.

Tel.: +1 7324169590

13 American Way Suite 15

USA - NJ 08884 Spotswood

e.mail: fleet089@hotmail.com



Safety Data Sheet

acc. to OSHA HCS

Reviewed on 02/28/2023 Printing date 02/28/2023

1 Identification

- · Product identifier
- · Trade name: Mipa WBS Beschleuniger
- · Application of the substance / the mixture Accelerator
- · Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

MIPA SE Am Oberen Moos 1 D-84051 Essenbach Tel.: +49(0)8703-922-0

Fax.: +49(0)8703-922-100

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

Emergency telephone number:

International: 011 49(0)700 24112112 (MIP)

US: +1 872 5888271 (MIP)

US Emergency Telephone Number (for transportation incidents only): 1-800-535-5053 (Infotrac)

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



Eye Irritation 2A H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:
- acetone
- · Hazard statements

H225 Highly flammable liquid and vapor. H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves/protective clothing/eye protection/face protection. P280

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

(Contd. on page 2)



acc. to OSHA HCS

Printing date 02/28/2023 Reviewed on 02/28/2023

Trade name: Mipa WBS Beschleuniger

(Contd. of page 1)

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 3 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
67-64-1	acetone	50-100%
64-17-5	ethanol	≥25-<50%

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)



acc. to OSHA HCS

Printing date 02/28/2023 Reviewed on 02/28/2023

Trade name: Mipa WBS Beschleuniger

(Contd. of page 2)

· Advice for firefighters

· Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:		
67-64-1	acetone	200 ppm
64-17-5	ethanol	1,800 pp
75-65-0	2-methylpropan-2-ol	150 ppm
78-93-3	Methyl ethyl ketone	200 ppm
646-06-0	1,3-dioxolane	60 ppm
PAC-2:		
67-64-1	acetone	3200* pp
64-17-5	ethanol	3300* pp
75-65-0	2-methylpropan-2-ol	1,300 pp
78-93-3	Methyl ethyl ketone	2700* pp
646-06-0	1,3-dioxolane	190 ppm
PAC-3:		
67-64-1	acetone	5700* ppn
64-17-5	ethanol	15000* pp
75-65-0	2-methylpropan-2-ol	8000* ppn
78-93-3	Methyl ethyl ketone	4000* ppn
646-06-0	1,3-dioxolane	1,000 ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)



acc. to OSHA HCS

Printing date 02/28/2023 Reviewed on 02/28/2023

Trade name: Mipa WBS Beschleuniger

(Contd. of page 3)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: 500 ppm Long-term value: 250 ppm

A4, BEI

64-17-5 ethanol

PEL Long-term value: 1900 mg/m³, 1000 ppm REL Long-term value: 1900 mg/m³, 1000 ppm

TLV | Short-term value: 1000 ppm

A3

· Ingredients with biological limit values:

67-64-1 acetone

BEI 25 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 5)



acc. to OSHA HCS

Printing date 02/28/2023 Reviewed on 02/28/2023

Trade name: Mipa WBS Beschleuniger

(Contd. of page 4)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

or mysical and enemical prope			
Information on basic physical and chemical properties			
· General Information · Appearance:			
Form:	Fluid		
Color:	According to product specification		
· Odor:	Characteristic		
· Odor threshold:	Not determined.		
· pH-value:	Not determined.		
· Change in condition			
Melting point/Melting range:	Undetermined.		
Boiling point/Boiling range:	56 °C (132.8 °F)		
Flash point:	<0 °C (<32 °F) (DIN 53213)		
Flammability (solid, gaseous):	Highly flammable.		
Ignition temperature:	425 °C (797 °F) (DIN 51794)		
Decomposition temperature:	Not determined.		
Auto igniting:	Product is not selfigniting.		
Danger of explosion:	Product is not explosive. However, formation of explosiv		
	air/vapor mixtures are possible.		
Explosion limits:			
Lower:	2.6 Vol %		
Upper:	15 Vol %		
Vapor pressure at 20 °C (68 °F):	233 hPa (174.8 mm Hg)		
Density at 20 °C (68 °F):	0.798 g/cm³ (6.659 lbs/gal) (DIN 53217)		
Relative density	Not determined.		

(Contd. on page 6)



acc. to OSHA HCS

Reviewed on 02/28/2023 Printing date 02/28/2023

Trade name: Mipa WBS Beschleuniger

		(Contd. of page
Vapor density	Not determined.	
· Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/wa	ater): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic at 20 °C (68 °F):	13 s (DIN 53211/4)	
Solvent content:		
VOC content:	41.20 %	
	810 g/l / 6.8 lb/gal	
Solids content (weight-%):	0.0 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

l	· LD/LC50 values that are relevant for classification:
Γ	67-64-1 acetone

Oral LD50 5,800 mg/kg (rat) Dermal LD50 20,000 mg/kg (rabbit)

- · Primary irritant effect:
- on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)			
64-17-5	ethanol		

NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 7)

1



acc. to OSHA HCS

Reviewed on 02/28/2023 Printing date 02/28/2023

Trade name: Mipa WBS Beschleuniger

(Contd. of page 6)

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

· UN-Number

· DOT, ADR, IMDG, IATA UN1263

· UN proper shipping name

· DOT

Paint related material

· ADR · IMDG, IATA **UN1263 PAINT RELATED MATERIAL**

PAINT RELATED MATERIAL

· Transport hazard class(es)

· DOT



· Class 3 Flammable liquids

(Contd. on page 8)



acc. to OSHA HCS

Printing date 02/28/2023 Reviewed on 02/28/2023

Trade name: Mipa WBS Beschleuniger

(Contd. of page 7) ·Label · ADR 3 (F1) Flammable liquids · Class · Label · IMDG, IATA 3 Flammable liquids · Class · Label 3 · Packing group · DOT, ADR, IMDG, IATA 11 · Environmental hazards: · Marine pollutant: No · Special precautions for user Warning: Flammable liquids · Hazard identification number (Kemler code): 33 · EMS Number: F-E,S-E · Stowage Category R · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: · Limited quantities (LQ) 5L · IMDG · Limited quantities (LQ) 5L · UN "Model Regulation": UN 1263 PAINT RELATED MATERIAL, 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

Section 313 (Specific toxic chemical listings):

75-65-0 2-methylpropan-2-ol

· Hazardous Air Pollutants

None of the ingredients is listed.

Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

(Contd. on page 9)



acc. to OSHA HCS

Reviewed on 02/28/2023 Printing date 02/28/2023

Trade name: Mipa WBS Beschleuniger

	(Contd. of page 8)
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
64-17-5 ethanol	

· EPA (Environmental Protection Agency)			
67-64-1	acetone		1
78-93-3	Methyl ethyl ketone		1
TLV (Threshold Limit Value)			
67-64-1	acetone	A4	50-100%
64-17-5	ethanol	A3	≥25-<50%
75-65-0	2-methylpropan-2-ol	A4	<1%
· NIOSH-Ca (National Institute for Occupational Safety and Health)			

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labeling:

acetone

· Hazard statements

H225 Highly flammable liquid and vapor. H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P210

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

· National regulations:

· Additional classification according to Decree on Hazardous Materials:

Class	Share in %
NK	50-100

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



acc. to OSHA HCS

Printing date 02/28/2023 Reviewed on 02/28/2023

Trade name: Mipa WBS Beschleuniger

(Contd. of page 9)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Contact:

· Date of preparation / last revision 02/28/2023

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3

* Data compared to the previous version altered.

USA